


1050 Series



Single Cover • Duct Cover • Multipart Cover



**SAFE LIFTING AID
RECOMMENDED**
See Cover Skate
pages 52-53

Barrel lifting points



1050 SERIES SPECIFICATIONS

FLOOR FINISHES:	All types of hard floor finish: concrete or natural stone. Specifically for use in internal/external areas where vehicle access is required.
PERFORMANCE:	Heavy-duty vehicles up to 6.5 tonne (6,500kg) pneumatic tyre wheel load. Suitable for both internal and external hard floors.
FEATURES and BENEFITS:	Can be fitted quickly and unobtrusively, ensuring minimum disruption. Unique cover sections are tapered for easy removal, frame sections give a good key to bedding mortar. Double sealed with socket head securing bolts complete with all necessary removable sealing cross-members and support beams (where necessary). Recessed support beam pockets (where necessary). Lifting blocks are anchored to the inner frame. Stainless steel securing bolts are stiletto heel proof. Provides easy access to underfloor services using lifting keys or Cover Skate.
FIRE RATING:	To BS 476: Part 20: 1987 - 3 hours for Single cover, 2 hours for Duct and Multipart covers.
SIZES:	See pages 6-7.
WEIGHT:	Approx. 200kg/m ² when filled with concrete.
INSTALLATION:	Go to www.bilcoul.co.uk



Stainless steel floor access covers
for demanding environments and
high traffic areas