

Bifold Doors

Manufactured to the highest level of precision in our state of the art factory, we have years of experience in making bifold door sets up to 8 metres in length and configurations, including complicated bowed track and right angled layouts.

All doors come with secure multi-point locking and adjustable hinges as standard, available in a range of finishes.

Timber Type

- Engineered Siberian Larch
- Engineered and solid Sapele
- European Oak

Standard Section Dimensions

- Frame depth – 93mm
- Sash Depth – 60mm
- Frame Jamb Width – 69mm
- Leaf Stile Width - 95mm

Mould & Fenestration Options

Frame Mould - Square

Sash Moulds - Ovolo, Ogee, Lambs Tongue, Square

- 18mm plant on bonded bar fenestration
- 44mm through bar fenestration
- 26mm through bar for slim line or single glazing

Glazing

- 24mm double glazed sealed units manufactured to a 4-16-4 configuration
- Toughened safety glass as standard
- Slim line 14mm DGU's or single glazing for listed buildings
- Factory glazed using a fully sealed system
- Low emissivity, solar control, tinted, easy-clean, obscure and laminated also available

Paint Finish

Timber is treated with three coats of factory applied Teknos, micro-porous paint providing a fully finished product. A choice of standard paint colours are available. Special colours can also be produced to match any sample or RAL reference number. We can also provide a combination of two-tone internal/external.

Bifold Operating Gear

- Centor bottom-rolling track system
- Externally stacking door leaves
- Bearings, tapered rollers and angled track are concealed by a protective gasket
- Cleaning sweepers to remove debris
- Drainage weep holes

Locking Gear

Designs with master and slave doors can also operate as traditional a French or single door system with multipoint, espag locking. Folding door systems are complemented with Centor locking systems with Twinpoint lock and dropbolts.

Section Detail

