

FLUSHER DISINFECTOR

Ninjo™



With its attractive design, easy operation and excellent disinfection performance, Ninjo is a reliable choice to support your infection control routine.

Ninjo cleans receptacles with a series of high pressure water cycles delivered through strategically located fixed and rotating nozzles, followed by a thermal steam disinfection phase to achieve effective cleaning and disinfection results.

Available in a wide selection of modular units and material finishes, Ninjo offers a high level of design flexibility to suit your needs and preference.

Key features



FLEXIBLE DESIGN

Ninjo is available in a colourful polymeric material or in stainless steel finish and is available as a free standing, wall mounted, or under-counter unit.

DRYING AND COOLING FAN

Built-in drying and cooling fan dries containers quickly and cools them with HEPA-filtered (H13) air.

A₀ VALUE DISPLAY

The control panel clearly indicates the disinfection level, allowing you to easily keep track of the disinfection progress.

REMAINING TIME

The remaining time sequence display allows staff to check on cycle progress, enabling them to plan their workflow.

PIPE SYSTEM DISINFECTION (PSD)

The entire pipe and nozzle system is disinfected at the end of every cycle, reducing the risk of contamination.

PRODUCT INFORMATION		
Model	Measurements	Weight
Free standing	450 x 580 x 1320 mm	90 kg (198 lbs)
Wall-mounted	450 x 580 x 1320 mm*	70 kg* (155 lbs*)
Under counter	450 x 620 x 870 mm	70 kg (155 lbs)
Noise level	53 dB(A) accoprdingly to EN ISO 3747:200	
Max external temperature	40°C (100°F)	

Electrical connection	230V, 1N, 50 Hz, 1x16A
Energy consumption	0,16 kWh/cycle
Water consumption	Economy program 11 liters/cycle ±10 % Normal program 18 liters/cycle ±10 %
Water connection	Pressure 1-8 Bar (14-116 PSI) 15 mm (1/2"), Rate of flow >0,3 l/s
Drain connection	Wall ø 90 mm or 110 mm (3 1/2 or 4 1/4") Floor ø 90 mm or 110 mm (3 1/2 or 4 1/4")

*Not including wall mounts and frame.