



Poplar/Ilomba construction giving significant weight saving and very high quality faces.

Our **+** Hanson Lightweight Plywood offers stability, ease of cutting and machining and most importantly low density.

+ Hanson Lightweight Plywood is available in a number of thicknesses as either Poplar throughout or as an exotic Ilomba faced, Poplar core combi-product. Poplar throughout offers the user a light weight, light colour, high homogeneity with a barely perceptible grain. Whereas the pinker hue of the Ilomba face offers versatility and ideal support for decorative coating materials.

Applications

Interior use - general joinery, shop/bar fitting, laminating, veneering, furniture, motorhomes, caravans, portable buildings.

SPECIFICATION DETAIL:

Thicknesses (mm)	3mm-25mm (Poplar) ; 3mm -15mm (Ilomba)
Dimensions	2440 x 1220/2500 x 1220/ 3050 x 1220
Average Density	400 Kg/m ³ ± 10%
Manufactured to	EN 636-1
Glue Bond	EN 314-2 Class 1 (Interior)
Formaldehyde Release	Class E1 (Tested to EN 717-2)
Moisture Content	8%-13%
Veneers	High Quality Face and Core
Environmental Certification	PEFC 100%
European Timber Regulation (EUTR) status	Compliant - Sourced within EU
CE Marked	BS EN 13986
Material Safety Data Sheet	Available

CONTACT:

Drakes Industrial Estate
Shay Lane, Halifax
West Yorkshire
HX3 6RL

Tel: 01422 330444
Fax: 01422 330706
Email: sales@hanson-plywood.co.uk
www.hanson-plywood.co.uk



For more information visit:
www.hanson-plywood.co.uk