

Product specification Composite doors



THE HATHERSAGE B-RATED SPECIFICATION (A-RATED AVAILABLE)

Frame profile

- Choice of:
 - Standard (EWS 032)
 - Large (EWS031)

Reinforcements

- PVC-U Thermal Inserts

Accreditations

- Secured By Design (subject to specification)
- PAS 23/24
- BM Trada Q Mark

Glass options

- Triple-glazed and double glazed options
- Choice of leading colour

Colour options

Standard door colours



Heritage door colours



Contemporary door colours



Door frame colours



Furniture

- Letterplates, handles, chains, spy-holes, numbers and knockers
- Choice of White, Gold, Chrome, Satin Silver and Satin Black stainless steel finishes*, backed by 25-year guarantee (*excludes White and Satin Black)

Min / max sizes

Doors with large outer frame

Width		Height (ali low-threshold)		Height (PVC-U bottom)	
Min	Max	Min	Max	Min	Max
860	1012	1979	2089	2021	2130

If door has GRP side panel and an aluminium low-threshold, **min height = 2020**. All heights are **reduced by 3mm** if open out aluminium low-threshold

If door has GRP side panel and PVC-U bottom, **max height = 2121**

Doors with standard outer frame

Width		Height (ali low-threshold)		Height (032 full outer)		Height (031 threshold)	
Min	Max	Min	Max	Min	Max	Min	Max
830	982	1964	2074	1991	2100	2006	2115

If door has GRP side panel and an aluminium low-threshold, **min height = 2005**. All heights are **reduced by 3mm** if open out aluminium low-threshold

If door has GRP side panel and PVC-U bottom, **max height = 2091**

032 is **15mm smaller** on both faces

GRP side panels

Min width	Max width	Height
410	475	To suit door

All side lights are separate.
Sizes include outer frame and coupler


Top lights

Transom height from bottom of door

Aluminium low-threshold		PVC-U bottom	
Min	Max	Min	Max
1945	2054	1971	2080

Dimensions to centre of transom. Doors over 2500mm will have separate top lights

Glazing sizes



The Hathersage

- Twin top cassettes
202mm x 152mm
- Mid panel cassettes
202mm x 578mm