



### Piccolo and Piccolo Premium

Ready to install element

**Stairs:**

Scissor unit and treads: Aluminium  
 Load bearing capacity per tread 150 kg or 350 kg/m<sup>2</sup> of the entire component  
 Tread depth: 8cm

**Standard sizes:**

Available in four height and two width options.  
 Refer to tables below for details.

Aperture size (width) min. cm	Tread width
from 37	28
from 42	33

#### Piccolo

Aperture length depends on the number of treads		Space required in cm	
Treads	Aperture size (length) min. cm	Floor to ceiling height "A"	Setdown point with α = 20° "B"
9	51	200 - 215	82 - 91
10	55	215 - 240	91 - 100
11	58	240 - 265	100 - 109
12	62	265 - 290	109 - 118

#### Piccolo Premium

Aperture length depends on the number of treads		Space required in cm	
Treads	Aperture size (length) min. cm	Floor to ceiling height "A"	Setdown point with α = 20° "B"
9	55	200 - 225	82 - 91
10	62	225 - 250	91 - 100
11	66	250 - 275	100 - 109
12	70	275 - 300	109 - 118

NOTE: ALL INFORMATION CONTAINED IN THIS DOCUMENT IS STRICTLY CONFIDENTIAL. THIS DRAWING IS THE PROPERTY OF PREMIER LOFT LADDERS AND MUST NOT BE REPRODUCED WITHOUT PRIOR PERMISSION.



PREMIER LOFT LADDERS  
 2 Dawson Drive,  
 Trimley St Mary,  
 Felixstowe, Suffolk. IP11 0YW  
 Tel: 0845 9000 195  
 Fax: 01394 214413  
 www.premierloftladders.co.uk

© All rights reserved. Report all discrepancies. Do not scale drawings.

First Issue	Date	Name	Piccolo and Piccolo Premium	Scale 1:10
A	25.11.2016	JP		
B	20.07.2017	JP		

Other sizes and different ceiling heights are available on request

**6000416**

The data on the drawings is for information only. All dimensions must be checked on site. No responsibility is taken for errors.