



### Supreme Electric with wooden hatchbox

**Ready to install element**

**Safety tested:** Tested according to DIN En 14975 by TÜV Süd

**Airtightness (a value):** class 4 - 600pa pressure tested to DIN EN 12207 by ift Rosenheim

**Thermal properties:** U-Value 0.58 W/m²K  
Calculation of the isolated area according to EN ISO 12567-1 by ift Rosenheim

**Stairs:**  
Scissor unit: die-cast aluminium  
Load bearing capacity per tread: 200kg or 500kg/m² of the entire component.  
Tread depth: 14cm (16cm)

**Custom sizes:**  
Custom sizes are available on request

Aperture length depends on the number of treads		Space required in cm		
Treads	Aperture size (length)	Floor to ceiling height "A"	Setdown point "B"	Swivel range "C"
9	110 - 160	220 - 250	139 - 128	146
10	120 - 160	250 - 279	151 - 139	159
11	130 - 160	279 - 309	162 - 150	171
12	140 - 160	309 - 339	174 - 161	184
13	145 - 160	339 - 369	202 - 190	212
14	150 - 160	369 - 399	215 - 203	225
15	155 - 160	399 - 430	227 - 214	239

Hatchbox external dimensions = aperture size -2cm in the length, -1.5cm in the width

Standard sizes		
Aperture size length x width	Hatchbox height	Tread width
120 x 70 cm	24 cm	30 cm
130 x 70 cm	24 cm	30 cm
140 x 70 cm	24 cm	30 cm



PREMIER LOFT LADDERS  
2 Dawson Drive,  
Trimley St Mary,  
Felixstowe, Suffolk. IP11 0YW  
Tel: 0845 9000 195  
Fax: 01394 214413  
www.premierloftladders.co.uk

Other sizes and different ceiling heights are available on request	6000455	Supreme Electric with wooden hatchbox	Scale 1:10
--	---------	---------------------------------------	------------

The data on the drawings is for information only. All dimensions must be checked on site. No responsibility is taken for errors.

NOTE: ALL INFORMATION CONTAINED IN THIS DOCUMENT IS STRICTLY CONFIDENTIAL. THIS DRAWING IS THE PROPERTY OF PREMIER LOFT LADDERS AND MUST NOT BE REPRODUCED WITHOUT PRIOR PERMISSION.