

# CHARCON

## HARD LANDSCAPING

TEXTURED PAVING

TECHNICAL INFORMATION  
www.aggregate.com/andovertextured

## ANDOVER TEXTURED

### FLAG AND BLOCK PAVING



PREMIUM QUALITY FLAG AND BLOCK PAVING LANDSCAPING PRODUCT. ANDOVER TEXTURED IS FINELY TEXTURED AND AVAILABLE IN A LARGE RANGE OF SHADES AND SIZES TO GIVE STYLISH APPEAL AND EXCEPTIONAL DURABILITY AT AN AFFORDABLE PRICE.

Incorporates uniquely formulated Cornish aggregates to maximise performance, durability and aesthetics offering the hard wearing characteristics of granite at an affordable price.

Range of shades can be used to complement and contrast one another.

13 flag and block paving sizes provides optimum design flexibility and strong visual appeal in virtually any location.

Available as an Infiltra concrete block permeable paver (CBPP).

#### APPLICATIONS

Suitable for high volume and prestigious pedestrian areas, town centres, shopping precincts and footways as well as occasional car or mechanical sweeper overrun, footways with cars and HGV vehicle or service areas. Refer to the relevant sections of BS7533 for correct design and applications. Refer to technical department for advice on your given application – telephone 01335 372222.

#### MANUFACTURING STANDARD

Andover Textured is manufactured using a semi-dry process. Flag paving is manufactured in accordance with and complies with all relevant sections of BS EN 1339: Precast concrete flags – requirements and test methods. Block paving is manufactured in accordance with and complies with all relevant sections of BS EN 1338: Precast concrete block paving – requirements and test methods.

Aggregate Industries fully operates an accredited Quality Assurance scheme, certified to BS EN 9001:2008 which is independently and regularly assessed by BSI (British Standards Institution). All Aggregate Industries manufacturing sites are also certified to BS EN 14001:2004 Environmental Management Systems

#### PERFORMANCE WITH SLIP RESISTANCE

Unpolished slip resistance values, when tested in accordance with BS EN 1339 and BS EN 1338, annex I – method for the determination of unpolished slip resistance value, are available on request. The product is classified as having a low potential for slip.


Polished slip resistance values can be provided on request.

#### COMPLEMENTARY PRODUCTS

Eco Countryside kerb and Countrysetts.



#### COLOUR SWATCH



- 1. White
- 2. Light Grey
- 3. Silver Grey
- 4. Midnight Grey
- 5. Cream
- 6. Chestnut
- 7. Oak
- 8. Silver Fleck

PRODUCT DATA														
Size (mm)	600x600	450x450	450x450	400x400	400x200	600x200	300x300	300x200	300x100	200x200	200x100	100x100	200x100	Mixed
Thickness (mm)	50	70	50	65	65	80	80	80	80	80	80	80	60	50
Weight (kg)	44	38.7	23.5	25	12.5	21	16.5	11	5.5	7.3	3.8	1.7	2.8	n/a
Units/m <sup>2</sup> (approx)	2.78	4.94	4.94	6.25	12.50	8.33	11.11	16.67	33.33	25	50	100	50	n/a
No. per pack	28	36	40	48	96	36	54	108	216	160	320	560	384	80
M <sup>2</sup> /pack (approx)	10.08	7.29	8.10	7.68	7.68	4.32	4.86	6.48	6.48	6.40	6.40	5.60	7.68	7.68
Pack weight (T)	1.23	1.39	0.94	1.00	1.20	0.76	0.89	1.18	1.18	1.17	1.16	1.00	1.08	0.92
Colours	Wh*, LG, SG*, MG, Cr*, Che*, Oa*, SF	Wh*, LG*, SG*, MG*, Cr*, Che*, Oa*, SF*	Wh*, LG, SG, MG, Cr, Che*, Oa*, SF	Wh*, LG, SG*, MG, Cr, Che*, Oa*, SF	Wh*, LG*, SG*, MG, Cr*, Che*, Oa*, SF*	Wh*, LG, SG*, MG, Cr*, Che*, Oa*, SF	Wh*, LG*, SG*, MG, Cr*, Che*, Oa*, SF*	Wh*, LG*, SG*, MG, Cr*, Che*, Oa*, SF	Wh*, LG*, SG*, MG*, Cr*, Che*, Oa*, SF	Wh*, LG*, SG*, MG, Cr*, Che*, Oa*, SF	Wh*, LG, SG, MG, Cr*, Che*, Oa*, SF	Wh*, LG*, SG*, MG, Cr*, Che*, Oa*, SF	Wh*, LG*, SG*, MG, Cr*, Che*, Oa*, SF	Wh*, SG*, MG*, SF*
Chamfered	Pencil	Pencil	Pencil	Pencil	Pencil	Pencil	Pencil	Pencil	Pencil	Pencil	Pencil	Pencil	Pencil	Pencil

Wh - White / LG - Light Grey / SG - Silver Grey / MG - Midnight Grey / Cr - Cream / Che - Chestnut / Oa - Oak / SF - Silver Fleck.

\* MTO products is a minimum of 600m<sup>2</sup> for one flag size and 1200m<sup>2</sup> for two flag sizes. 350m<sup>2</sup> for one block size, 600m<sup>2</sup> for two block paving sizes, 700m<sup>2</sup> for three sizes and 800m<sup>2</sup> for four sizes.

Contact the sales office for step insert information.

Mixed Pack contents:

600 x 200 = 32  
400 x 200 = 48



Q24 and Q25. For NBS clauses, refer to Aggregate Industries technical services.

# ANDOVER TEXTURED

## FLAG AND BLOCK PAVING

### SUSTAINABILITY AND LOCAL SOURCING

**ENERGY USE:** Aggregate Industries is at the forefront of sustainability and has committed to reduce carbon emissions by 20% by 2016 based on a 2012 base line.

**RECYCLABLE:** 100% of the product can be recycled thus reducing the amount of material that is sent to landfill.

#### MANUFACTURING LOCATION:

Produced in the UK under strict environmental and social legislation.

**RESPONSIBLE SOURCING:** Aggregate Industries is the first company in the world to achieve accreditation to the BES 6001 Framework Standard for the Responsible Sourcing of Construction Products.

Aggregate Industries has achieved a 'Very Good' rating for major product groups. The BES 6001 standard assesses:

Quality management.

Environmental management.

Health and safety management.

A range of social and environmental issues.

### KEY AGGREGATE AND RECYCLED CONTENT

Andover Textured is manufactured from specially selected aggregates in a semi-dry process and shot blasted.

### GENERIC GREEN GUIDE RATING\*

Concrete paving flags (60mm with a prepared recycled sub-base) - **A+ rated**.

Concrete paving flags (60mm with a prepared sub-base) - **A rated**.

Concrete block pavers (80mm) over prepared recycled sub-base - **A rated**.

Concrete block pavers (80mm) over prepared sub-base - **B rated**.

### POLICIES

Aggregate Industries' policies on the environment and community, health and safety and sustainable solutions for different product applications can be viewed on our website [www.aggregate.com](http://www.aggregate.com)

### DESIGN AND INSTALLATION

For flag pavement design guidance refer to BS 7533 Part 8, For successful installation refer to BS 7533 Part 4. For specific design, installation and maintenance guidance, please contact our technical department on 01335 372222.

For block paving pavement design guidance refer to BS 7533 Parts 1 & 2. For successful installation refer to BS 7533 Part 3. For specific design, installation and maintenance guidance, please contact our technical department on 01335 372222.

### MAINTENANCE AND CLEANING

After laying light coloured paving on site, care should be taken to protect from dirt and detritus while the remaining construction works are completed.

Aggregate Industries can supply on request advice on specific stain removal and general maintenance, suitable cleaning products and referrals to specialist cleaning companies.

### COSHH DATA

Full COSHH data on the Charcon range of products is available on request. Please call the technical helpline on 01335 372222.

### TECHNICAL SUPPORT

DETAILED GUIDANCE AND ASSISTANCE WITH THE PREPARATION OF SPECIFICATION OF THE CHARCON RANGE OF HARD LANDSCAPING PRODUCTS, INCLUDING MODEL CLAUSES, IS AVAILABLE THROUGH THE SALES OFFICE. A FREE TECHNICAL DESIGN SERVICE IS ALSO AVAILABLE.

**FOR FURTHER INFORMATION, PLEASE REFER TO OUR TECHNICAL SERVICES ON 01335 372222.**

\*Ratings based upon generic green guide values (2009) supplied by BRE Global Ltd, [www.thegreenguide.co.uk](http://www.thegreenguide.co.uk)

The information contained within this publication was accurate at time of production. However, Aggregate Industries reserves the right to introduce modifications or changes to detail at any time without notice. No charge is levied for this publication or advice therein, and accordingly the company, its employees and authorised agents can accept no liability whatsoever, either indirectly or directly arising from the use of its products.

### Charcon

Aggregate Industries, Hulland Ward,  
Ashbourne, Derbyshire DE6 3ET

Tel: +44 (0)1335 372 222

Fax: +44 (0)1335 370 074

Email: [landscaping@aggregate.com](mailto:landscaping@aggregate.com)

[www.aggregate.com](http://www.aggregate.com)

