

Hush Acoustics - Floating Flooring

HUSH PANEL 12/14



Hush-Panel 12/14 has been designed as a thinner impact overlay board to minimise floor build where required. The upper layer provides a uniformly smooth surface for application of floor finishes with a unique 3/5mm acoustic membrane to the underside designed for use on top of concrete floors, thereby eliminating the problems of under-screed layers which may be bridged during site installation.

ACOUSTIC PERFORMANCE

Hush Panel 12 Weighted Sound Reduction ALW = 18db

Hush Panel 14 Weighted Sound Reduction ALW = 21db

Test data available on request



PRODUCT DATA

- Can be laid over concrete and timber floors.
- Comprises 9mm Moisture Resistant tongued and grooved MDF with 3/5mm resilient cork rubber layer
- Overall Board Dimensions 1200mm x 600mm x 12/14mm
- FFL over floor deck 12/14mm

SUITABLE FOR:



FEATURES

- ✓ Excellent acoustic performance
- ✓ Ideal for areas with limited room height
- ✓ Refurbishment and New Build
- ✓ Building Regulations Part E (England and Wales), Section 5 (Scotland) and Part G (Northern Ireland)

HUSH ACOUSTICS

TEL: 0151 933 2026

EMAIL: info@hushacoustics.co.uk

www.hushacoustics.co.uk

 [hush-acoustics](https://www.linkedin.com/company/hush-acoustics)

 [@hushacoustics](https://twitter.com/hushacoustics)  [hushuk.acoustics](https://www.facebook.com/hushuk.acoustics)

44 Canal Street, Bootle, Liverpool L20 8QU
Offices also based in London and Yorkshire



HUSH ACOUSTICS