# Mesh for Soffit Ventilation and Cladding

**Go to web page**

## Insect Mesh

- Available in Fibreglass or Stainless Steel rolls
- Fibreglass mesh is made from woven fibreglass yarn, with a pvc coating, 18x16 gauge.
- Stainless Steel insect mesh is woven steel, 304 grade, 16x16 gauge, with wire diameter of 0.228mm
- Available in a range of easy to use widths and roll lengths
- Specified to keep insects out of the gaps behind external cladding
- Allows natural ventilation
- Suitable for internal or external application
- Non-combustible and will not rust or corrode.

## Rodent Mesh

- Extra tough woven stainless steel, 304 grade, 12x12 gauge
- Wire diameter of 0.56mm, Aperture size 1.56mm
- Available in 1m or 150mm rolls
- Specified to keep rodents out of the gaps behind external cladding
- Allows natural ventilation
- Suitable for internal or external application
- Non-combustible and will not rust or corrode

300mm

150mm

100mm

50mm

Fibreglass PVC coated

150mm

75mm

Stainless Steel - Insect Mesh

## Fixing Methods for Soffit Ventilation for Cladding

The mesh can be fixed with staples, battening, tacks or with a bead of silicone.

Fascia — Soffit — Mesh

Fascia — Mesh — Soffit

Fascia — Mesh

Fascia — Drilled hole — Soffit — Mesh

Fascia — Mesh — Soffit

Fascia — Mesh — Soffit — Drilled hole

Fascia — Mesh — Soffit

## Fixing Method for Cladding

## Mesh Types

The swatches below are to scale

### Fibreglass PVC Coated

18x16 gauge
Grey or Black
Aperture: 1.6mm x 1.4mm
Open Area: 59%
Roll lengths: 45m to 50m
Roll widths: 50mm, 75mm, 100mm, 150mm, 200mm, 300mm

### Stainless Steel-Insect Mesh

304 Grade, 16x16 gauge
Silver
Wire Diameter: 0.228mm
Aperture: 1.36mm
Open Area: 73%
Roll length: 30m
Roll widths: 1.2m and narrow rolls for soffits 75mm, 100mm, 150mm, 200mm

### Stainless Steel-Rodent Mesh

304 Grade, 12x12 gauge
Silver
Wire diameter: 0.56mm
Aperture: 1.56mm
Open area: 54%
Roll length: 30m
Roll width: 1m or 150mm

The Flyscreen Company   T: 01454 238288   sales@flyscreen.com