



Hush FR Roofing Membrane

Generated on 23.08.2019

Detailed description

Rubber roofing membrane for use in conjunction with Hush Acoustics flat roof solutions in the reduction of airborne and impact noise.

Product guidance - As Standard

Material:

Recycled rubber crumb bonded with polyurethane.

Roll size (l x w):

6 x 1.25 m.

Thickness:

10 mm.

Colour:

Black/ beige.

Technical properties:

- Tensile strength (to DIN EN ISO 1798): 0.8 N/mm².
- Elongation at break (to DIN EN ISO 1798): 125%.
- Density (approximate): 770 kg/m³.
- Service temperature: -30 to +80°C.
- Fire resistance (to BS EN 13501-1): Efl.

Product specification

Manufacturer

- Name: Hush Acoustics
- Web: www.hushacoustics.co.uk
- Email: info@hushacoustics.co.uk
- Tel: +44 (0)151 933 2026
- Fax: +44 (0)151 944 1146
- Address: 44 Canal Street, Liverpool, Merseyside L20 8QU

Product reference Hush FR Roofing Membrane



HUSH ACOUSTICS
Sound Insulation Products and Systems

Hush Acoustics
44 Canal Street
Liverpool
Merseyside
L20 8QU

Tel: +44 (0)151 933 2026

www.hushacoustics.co.uk
info@hushacoustics.co.uk



ribproductselector.com

A building products library for construction industry professionals

NBS Plus