



HD1056 Block Cavity Block Wall

Generated on 27.01.2020

Detailed description

A high performing block cavity wall system.

Features:

- Can be used in new build, conversion and refurbishment developments.
- Provides a one-hour fire resistance.
- Building Regulations Approved Document E (E&W), Technical Handbook Section 5 (Scotland) and Technical Handbook G (Northern Ireland) compliant.
- A tried and tested method of creating a dense block cavity block masonry wall.
- Excellent acoustic performance due to the mass of the blocks and the clear 100 mm cavity.

Components:

- Block cavity wall (1900 kg/m³) - supplied by others.
- 15 mm thick Gyproc Soundbloc plasterboard on both sides - supplied by others.
- Hush Acoustic Sealant - to seal perimeters.

Product guidance - As Standard

Components:

- Hush Acoustic Sealant:

- Description: Fire rated acoustic sealant/ adhesive.
- Material: Intumescent acrylic.

Acoustic performance:

- Airborne (Dntw): 58 dB.
- Airborne (Dntw +Ctr): 48 dB.

Product specification

Manufacturer

- Name: Hush Acoustics
- Web: www.hushacoustics.co.uk
- Email: info@hushacoustics.co.uk

Hush Acoustics



HUSH ACOUSTICS
Sound Insulation Products and Systems

Hush Acoustics

44 Canal Street
Liverpool
Merseyside
L20 8QU

Tel: +44 (0)151 933 2026

www.hushacoustics.co.uk
info@hushacoustics.co.uk



ribaproductselector.com

A building products library for construction industry professionals

NBS Plus

- Tel: +44 (0)151 933 2026

- Fax: +44 (0)151 944 1146

- Address: 44 Canal Street, Liverpool, Merseyside L20 8QU

Product reference HD1056 Block Cavity Block Wall