



Surespan SRHP Roof Hatch - Premium

Generated on 21.02.2020

Detailed description

Thermally-broken, single-leaf access hatch.

Features and benefits:

- Provides safe and convenient roof access.
- Enhanced thermal insulation; the upstand is filled with 50 mm chlorofluorocarbon (CFC) and hydrochlorofluorocarbon (HCFC)-free polyisocyanurate Kingspan insulation, offering high performance and a thermal transmittance (U-value) of 0.43 W/m²K.
- Includes gas spring assisted opening, and incorporates a safety hold open stay/ grip handle to prevent accidental closure.
- Supported by heavy-duty stainless steel hinges and fixings.
- The aluminium curb liner provides improved insulation properties.
- The lid is held shut by a heavy duty grade 1.4401 (316) stainless steel Cablock.
- Designed to be easily operated by one person.
- Sureclip FlashFast membrane fixing system.
- Double unbroken seals.
- 10-year inclusive warranty.

Applications:

Can be used in the following commercial and residential locations:

- Schools.
- Hospitals.
- Hotels.
- Office buildings.
- Shopping centres.
- Prisons.
- Factories/ manufacturing plants.
- Fast-food restaurants.
- Gyms.
- High-rise housing.
- Storage facilities/ warehouses.

Product guidance - As Standard

Overall height (with lid open):

- 600 x 600 mm: 1065 mm.
- 750 x 1500 mm: 1215 mm.

Trade Access Panels



Trade Access Panels
Units 2&3 Oak Tree Court
Brookfield Drive
Cannock
WS11 0JN

Tel: +44 (0)1922 500 145

tradeaccesspanels.co.uk
sales@tradeaccesspanels.co.uk



- 750 x 2500 mm: 1215 mm.
- 750 x 3300 mm: 1215 mm.
- 800 x 800 mm: 1265 mm.
- 900 x 750 mm: 1365 mm.
- 900 x 900 mm: 1365 mm.
- 1000 x 1000 mm: 1465 mm.
- 1200 x 1200 mm: 1665 mm.

Product specification

Manufacturer

- Name: Trade Access Panels
- Web: tradeaccesspanels.co.uk
- Email: sales@tradeaccesspanels.co.uk
- Tel: +44 (0)1922 500 145
- Fax: +44 (0)1922 500 145
- Address: Units 2&3 Oak Tree Court, Brookfield Drive , Cannock WS11 0JN

Product reference	Surespan SRHP Roof Hatch - Premium
Material	Aluminium - Standard. Aluminium extrusions in 6063-T6. Provides increased thermal insulation. Stainless steel - On request.
Size	600 x 600 mm - Overall size (including fixing flange): 840 x 840 mm. Weight: 42 kg. 750 x 1500 mm - Overall size (including fixing flange): 990 x 1640 mm. Weight: 75 kg. 750 x 2500 mm - Overall size (including fixing flange): 990 x 2740 mm. Weight: 135 kg. 750 x 3300 mm - Overall size (including fixing flange): 990 x 3540 mm. Weight: 160 kg. 800 x 800 mm - Overall size (including fixing flange): 1040 x 1040 mm. Weight: 54 kg. 900 x 750 mm - Overall size (including fixing flange): 1140 x 990 mm. Weight: 58 kg. 900 x 900 mm - Overall size (including fixing flange): 1140 x 1140 mm. Weight: 60 kg. 1000 x 1000 mm - Overall size (including fixing flange): 1240 x 1240 mm. Weight: 66 kg. 1200 x 1200 mm - Overall size (including fixing flange): 1440 x 1440 mm. Weight: 94 kg.



Finish

- Internal Not required - For stainless steel variants.
Mill finish - Standard, for aluminium variants.
Powder-coated - For aluminium variants.
Consult manufacturer and insert
requirement.

- External Not required - For stainless steel variants.
Mill finish. - Standard, for aluminium
variants.
Powder-coated - For aluminium variants.
Consult manufacturer and insert
requirement.

Locking

L01 Internal Opening Only - Cablock,
internal opening only.
L02 Cablock with hasp and staple - Internal
Cablock with hasp and staple.
L04 External Handle/ Cablock - Internal
Cablock with padlockable external handle.
L06 European Deadlock - External key,
internal thumb turn lock.
L07 European Deadlock - Internal/ external
key lock internal opening.

Upstand

200 mm
300 mm - Standard.