



## Tile Access Panel

Generated on 21.02.2020

### Detailed description

Access panel designed to integrate with existing tiling.

### Features and benefits:

- Includes a moisture board infill and concealed beaded perforated frame to take a ceramic tile.
- Manufactured to suit current tile and grout thickness.
- Can be specified with specific fire performance.
- 10-year inclusive warranty.

### Applications:

For integrating with tiled walls for a ceramic or marble finish in areas where regular maintenance to services is required.

Please note that the actual size of structural opening in the wall/ ceiling needs to be 10 mm larger than the overall panel size.

### Product guidance - As Standard

#### Material:

- Frame/ door tray: 1 mm-thick Zintec steel.
- Infill: 12 mm-thick moisture board.

#### Frame:

20 mm.

### Product specification

#### Manufacturer

- Name: Trade Access Panels
- Web: [tradeaccesspanels.co.uk](http://tradeaccesspanels.co.uk)
- Email: [sales@tradeaccesspanels.co.uk](mailto:sales@tradeaccesspanels.co.uk)
- Tel: +44 (0)1922 500 145
- Fax: +44 (0)1922 500 145
- Address: Units 2&3 Oak Tree Court, Brookfield Drive, Cannock WS11 0JN

**Product reference** Tile Access Panel

**Size** [ \_\_\_\_\_ ]

[Trade Access Panels](http://tradeaccesspanels.co.uk)



**Trade Access Panels**  
Units 2&3 Oak Tree Court  
Brookfield Drive  
Cannock  
WS11 0JN

Tel: +44 (0)1922 500 145

[tradeaccesspanels.co.uk](http://tradeaccesspanels.co.uk)  
[sales@tradeaccesspanels.co.uk](mailto:sales@tradeaccesspanels.co.uk)



<b>Finish</b>	[ ]
<b>Tiling</b>	
- Size	[ ]
- Thickness	[ ]
- Grouting	[ ]
- Adhesive thickness	[ ]
<b>Locking/ opening</b>	Budget lock with hinge Lift-out door Touch catch
<b>Hinges</b>	To the long side To the short side
<b>Fire rating</b>	Required - Consult manufacturer and insert requirements. Not required