



Aluminium Controllable Internal Louvre Grille 441

Generated on 25.02.2020

Detailed description

Slotted-plate aluminium ventilator, with hit-and-miss airflow control, for internal wall recess mount.

- Enables secure ventilation.
- Choice of finish.
- Standard sizes or made to measure.
- 5 mm projecting flange with recessed faceplate. 21 mm (maximum) flange overlap.
- Internal slide.
- Choice of cord, slide knob or rotating knob operation.

Product guidance - As Standard

Material:

Aluminium alloy: AlMgSi 0.5 to DIN 1748.

Product specification

Manufacturer

- Name: Renson Fabrications Ltd
- Web: www.rensonuk.net
- Email: info@rensonuk.net
- Tel: +44 (0)1622 754123
- Fax: +44 (0)1622 689478
- Address: Fairfax Units 1 - 5, Bircholt Road, Parkwood Industrial Estate, Maidstone, Kent ME15 9SF

Product reference	Aluminium Controllable Internal Louvre Grille 441
Dimensions (w x h without flange)	217 x 212 mm - Airflow 34 m ³ /h at 2 Pa. 248 x 212 mm - Airflow 38 m ³ /h at 2 Pa. 307 x 312 mm - Airflow 87 m ³ /h at 2 Pa. ___ x ___ mm As drawing ___
Control	Cord

Renson Fabrications Ltd



Creating healthy spaces

Renson Fabrications Ltd
Fairfax Units 1 - 5
Bircholt Road
Parkwood Industrial Estate
Maidstone
Kent
ME15 9SF

Tel: +44 (0)1622 754123

www.rensonuk.net
info@rensonuk.net



Rotating knob at ventilator
Slide knob at ventilator - Unit
width (maximum): 500 mm.

**Finish (aluminium
components)**

Anodized, bronze - 25 μ . Type
E6/ EV1 to DIN 17611.
Anodized, natural - 25 μ . Type
E6/ C34 to DIN 17611.
Polyester powder coating, RAL
colour ____, sheen ____ % -
60–70 μ .

Fixing

Screws - Standard option.
Spring clips - Nonstandard
option.

Other requirements

Mesh, 2.3 x 2.3 mm - Standard
option. Grade 304 stainless
steel.