

Double Glazed Replacement Window

Generated on 10.04.2020

SASH WINDOW SPECIALISTS

Ventrolla Sash Window Restoration

Ventrolla House Crimple Court Hornbeam Business Park Harrogate North Yorkshire HG2 8PB

Tel: +44 (0)1423 859323

www.ventrolla.co.uk info@ventrolla.co.uk

Detailed description

Purpose-made complete new timber double glazed window for replacing original windows.

Benefits:

- · Reduced energy costs.
- · Easy future maintenance.
- · Complies with Building Regulations Approved Document L.
- Perimeter sealing system tested to BS 6375-1 (withstands 71 mph winds).
- · Five year guarantee.
- · Aquamac/ QLON gasket weatherseals (casement windows).

Product guidance - As Standard

Material:

The replacement windows are manufactured from hardwood.

Finish:

Supplied sprayed with a high build base coat Teknos 3130 and an anti-stain primer Teknos Antique White, ready for final finishing coat by others.

Glazing:

Slim 16 mm (4/8/4) double glazed units with dual seal edge technology, with Saint-Gobain Planitherm Total+ Glass (outer pane) and Krypton gas filled cavity. The units comply with BS EN 1279 parts 1-6.

Construction:

The windows are manufactured using traditional carpentry methods, including 'through solid' glazing bars, which help to retain the windows authentic feel and look. Another main feature of the slim glazing unit is the reduced sightline of the spacer bar between the two panes of glass.

Ventrolla Sash Removal System (SRS):

To assist with future maintenance and painting, we install our patented Sash Removal System (SRS) that enables both the top and bottom sashes to be removed for redecoration and future maintenance.

Ventrolla Perimeter Sealing System (VPSS):

Includes unique VPSS draught proofing system which has been tested to BS 6375-1, Class 3, and withstand 71 mph winds. The system is fitted by routing grooves into the mid-rail and bottom-rail of the sashes, or within the inner edges of casement windows, to which a pile carrier is fitted and the appropriate size of weatherfin pile installed. New parting beads and staff



beads are fitted that also incorporate the weatherfin pile, creating a fully draught-proofed window.

Thermal performance (U-Value):

Centre pane: 1.3 Wm²K.
Total window: 1.6 Wm²K.

Options

Ironmongery:

Supplied with hardware, optional finishes and a range of styles are available.

Product specification

Manufacturer

- Name:	Ventrolla Sash Window Restoration	
- Web:	www.ventrolla.co.uk	
- Email:	info@ventrolla.co.uk	
- Tel:	+44 (0)1423 859323	
- Fax:	+44 (0)1423 859321	
- Address:	Ventrolla House, Crimple Court, Hornbeam Business Park, Harrogate, North Yorkshire HG2 8PB	
Product reference		Double Glazed Replacement Window
Туре		
Size		As drawing As schedule
Material		Hardwood
Glazing		16 mm double glazed units - 4/8/4 units with Krypton gas filled cavity.
Glazing spacer		Black White
Glazing bar		
Ventrolla Perimeter Sealing System (VPSS) location		Frame Sash
Ironmongery		