



22 mm Thermostatic Mixing Valve TS4753ECP

Generated on 19.08.2019

BRISTAN

Detailed description

22 mm thermostatic mixing valve.

Features:

- Ideal for group applications at pressures as low as 0.1 bar.
- Temperature control can be locked in position or allow adjustment.
- Automatic shut-off in the event of hot or cold water supply failure.
- Check valves and serviceable filters as standard.
- Operates at a maximum pressure differential of 10:1.

Approvals:

WRAS certified.

Product guidance - As Standard

Finish:

Chrome.

Pressures:

- Minimum pressure drop: 0.1 bar.
- Maximum dynamic pressure: 5 bar.
- Maximum static pressure: 10 bar.

Temperatures:

- Factory preset temperature: 43°C.
- Maximum hot water supply temperature: 80°C.

Product specification

Manufacturer

- Name: Bristan
- Web: www.bristan.com
- Email: specify@bristan.com
- Tel: +44 (0)844 7016273
- Fax: +44 (0)1827 254016
- Address: Birch Coppice Business Park, Dordon, Tamworth, Staffordshire B78 1SG

Bristan

Bristan

Birch Coppice Business Park
Dordon
Tamworth
Staffordshire
B78 1SG

Tel: +44 (0)844 7016273

www.bristan.com
specify@bristan.com



ribproductselector.com

A building products library for construction industry professionals

NBS Plus

Product reference TS4753ECP