



Speedfit Service Valve

Generated on 14.07.2020

Detailed description

Brass chrome plated service valves are suitable for use on hot and cold water systems and for central heating systems. Plastic service valves are suitable for hot and cold water only, 65° maximum. All valves are 1/4 turn open/ close, operated by a screwdriver slot.

Options

Plastic service valve:

- 15CV: 15 mm.
- 22SV: 22 mm.

Plastic service valves with tap connector:

- 15SVSTC: 15 mm x 1/2" Grey.
- 15SVSTC-W: 15 mm x 1/2" White.

Plastic angle service valve with tap connector:

- 15SVBTC: 15 mm x 1/2 " Grey.
- 15SVBTC-W: 15 mm x 1/2" White.

Brass service valve:

- 15HSV-BRASS: 15 mm.

Brass chrome plated service valve:

- 10 HSV: 10 mm.
- 15 HSV: 15 mm.
- 22 HSV: 22 mm.

Brass chrome plated service valve with tap connector:

- 15PTSV: 15 mm x 1/2".
- 22PTSV: 22 mm x 3/4".

Product specification

Manufacturer

- Name: John Guest Speedfit Ltd
- Web: www.speedfit.co.uk
- Email: info@johnguest.co.uk

John Guest Speedfit Ltd



John Guest Speedfit Ltd
Horton Road
West Drayton
Middlesex
UB7 8JL

Tel: +44 (0)1895 449233

www.speedfit.co.uk
info@johnguest.co.uk



- Tel: +44 (0)1895 449233

- Fax: +44 (0)1895 420321

- Address: Horton Road, West Drayton, Middlesex UB7 8JL

Product reference Speedfit Service Valve

Type

15CV
22SV
15SVSTC
15SVSTC-W
15SVBTC
15SVBTC-W
15HSV-BRASS
10HSV
15HSV
22HSV
15PTSV
22HSV
Contractor's choice
As drawing ____
As schedule ____