



150 mm Shiplap Cladding

Generated on 17.01.2020

Detailed description

150 mm cellular PVC shiplap cladding, comprising high impact PVC-UE (unplasticised expanded polyvinyl chloride) compound co-extruded onto a foamed PVC-UE cellular core.

Classified as 'Self extinguishing' (P), in accordance with BS 476-5.

Note that the product does not form a watertight or airtight facing. To achieve a waterproof barrier a breather membrane must be provided behind the cladding.

The insulation provided by the cladding and the cavity formed between the planks and the backing wall will improve the overall U-value of the wall construction.

Recommended method of fixing is A4 stainless steel cladding pins, 30 mm long, with 2.0 mm shank.

An extensive range of trims is available to suit all applications.

Product guidance - As Standard

Thickness:

7 mm (nominal).

Colour:

White. Foiled Mahogany, Golden Oak, Black Ash & Rosewood.

Finish:

Smooth semi-matt.

Product specification

Manufacturer

- Name: FloPlast Ltd
- Web: www.floplast.co.uk
- Email: sales@floplast.co.uk
- Tel: +44 (0)1795 431731
- Fax: +44 (0)1795 431188
- Address: Castle Road, Eurolink Business Park, Sittingbourne, Kent ME10 3FP

Product reference 150 mm Shiplap Cladding, Ref: C150

FloPlast Ltd

FloPlast Ltd
Castle Road
Eurolink Business Park
Sittingbourne
Kent
ME10 3FP

Tel: +44 (0)1795 431731

www.floplast.co.uk
sales@floplast.co.uk



Accessories

- [Butt joint trim, Ref: CT8]
- [Centre joint trim, Ref: CT7]
- [Drip trim, Ref: CT4]
- [Internal/External corner trim, Ref: CT5]
- [Starter trim, Ref: CT2]
- [Top edge trim, Ref: CT1]
- [Universal channel, Ref: CT3]