



## Durapine Timber Decking

Generated on 18.01.2020

### Detailed description

External Timber Decking.

### Product guidance - As Standard

The timber is kiln dried both before and after it has been pressure treated. This process pre-shrinks the timber, thereby providing stability and resistance to the movement typical of wet timber. It also allows the timber to be stained or finished immediately after installation. Treatment is to a preservative retention level of 0.4 lbs/ft<sup>2</sup>, ensuring that all decking boards are weatherproof, capable of resisting insect attack and suitable for contact with both ground and water.

#### Material:

Durapine Grade 1 Southern Yellow Pine

#### – Treatment:

Kiln dried both before and after preservative pressure treatment.

### Product specification

#### Manufacturer

- Name: Outdoor Deck Company Ltd
- Web: [www.outdoordeck.co.uk](http://www.outdoordeck.co.uk)
- Email: [sales@outdoordeck.co.uk](mailto:sales@outdoordeck.co.uk)
- Tel: +44 (0)20 8977 0820
- Fax: +44 (0)20 8977 0825
- Address: Unit 6, Teddington Business Park, Station Road, Teddington TW11 9BQ

**Product reference** Durapine Timber Decking

**Profile** Planed all round - Eased four edges.

#### Finished size

- Thickness x width 25 x 140 mm

- Length 3 m  
4.2 m

**Finish** None required



Outdoor Deck Company Ltd  
Unit 6  
Teddington Business Park  
Station Road  
Teddington  
TW11 9BQ

Tel: +44 (0)20 8977 0820

[www.outdoordeck.co.uk](http://www.outdoordeck.co.uk)  
[sales@outdoordeck.co.uk](mailto:sales@outdoordeck.co.uk)



**rib**productselector.com

A building products library for construction industry professionals

**NBS Plus**