



Stair Tread 02 Achil

Generated on 18.01.2020

Detailed description

Perforated stair tread manufactured from 2 mm thick galvanized steel. The O2 Achil benefits from a rolled front/ rear edge that both increases strength and protects the achilles tendon by preventing footwear from catching in use. Loading is designed in accordance with BS 4592 Part 0.

Applications:

For use in industrial, commercial and private staircases. The O2 Achil can also be used to make small landings on straight flights, by utilising standard sizes to suit the area.

Product guidance - As Standard

Thickness:

2 mm with 9 mm radius raised holes and 5 mm radius depressed holes.

Options

Depth:

Options are dependent on length and material of tread, consult manufacturer's literature for more information.

Product specification

Manufacturer

- Name: Elefant Gratings Ltd
- Web: www.elefantgratings.com
- Email: sales@elefantgratings.com
- Tel: +44 (0)1902 797110
- Fax: +44 (0)1732 885962
- Address: Enterprise Drive, Four Ashes, Wolverhampton, West - Midlands WV10 7DF

Product reference Stair Tread 02 Achil - Galvanized steel.

Length
400 mm - Height: 45 mm.
500 mm - Height: 45 mm.
600 mm - Height: 45 mm.
700 mm - Height: 45 mm.
900 mm - Height: 45 mm.
1000 mm - Height: 45 mm.
1100 mm - Height: 57 mm.
1200 mm - Height: 45 mm.

Elefant Gratings Ltd



Elefant Gratings Ltd
Enterprise Drive
Four Ashes
Wolverhampton
West - Midlands
WV10 7DF

Tel: +44 (0)1902 797110

www.elefantgratings.com
sales@elefantgratings.com



1500 mm - Height: 57 mm.
Special order - Insert requirements.

Depth

- 150 mm
- 200 mm
- 225 mm
- 250 mm
- 275 mm
- 300 mm