



Roller Shutter Armourguard N2

Generated on 12.11.2019

Detailed description

76 mm curved solid 22 gauge galvanized steel lath with 150 x 50 x 45 mm pitch apertures in a choice of 'brick bond' or 'in-line' patterns and designed for commercial applications where high vision and/ or ventilation is a requirement.

Product guidance - As Standard

Arrangement:

Vertical operation.

Shutter curtain:

76 x 0.71 mm curved solid steel 22 gauge lath with 150 x 50 x 45 mm pitch apertures.

Shutter box:

0.91 mm bright spangle galvanized pressed steel coil casing.

Product specification

Manufacturer

- Name: HAG Ltd. - The Door Specialists
- Web: www.hag.co.uk
- Email: info@hag.co.uk
- Tel: +44 (0)800 072 3444
- Fax: +44 (0)117 965 7773
- Address: 1 Oak Lane, Fishponds, Bristol BS5 7UY

Product reference Armourguard Type N2 Standard roller shutter

Shutter curtain

- Type 76 mm x 0.71 mm curved solid 22 gauge lath with 150 mm x 50 mm x 45 mm pitch apertures
- Pattern Brick bond
 Inline
- Finish Galvanized - Standard factory finish.
 Polyester powder coated - Optional factory finish.

[HAG Ltd. - The Door Specialists](#)



THE DOOR SPECIALISTS

HAG Ltd. - The Door Specialists

1 Oak Lane
Fishponds
Bristol
BS5 7UY

Tel: +44 (0)800 072 3444

www.hag.co.uk
info@hag.co.uk



Frame/ guides

- Type
 - 50 x 32 x 3 mm - For standard frame up to 3000 mm width.
 - 63 x 32 x 3 mm - For standard frame up to 5000 mm width.
 - 50 x 50 mm galvanized steel box section - For electrically operated shutters.
 - 76 x 50 mm galvanized steel box - For shutters over 200 kg.

- Finish
 - Galvanized - Standard factory finish.
 - Polyester powder coated - Optional factory finish.

- Operation**
 - Single phase electrical
 - Spring loaded manual
 - Three phase electrical

- Control**
 - Rocker switch
 - Security key switch