



Industrial Door Bi folding Q Door

Generated on 15.11.2019

Detailed description

A range of bi-folding panel doors, designed for mainly industrial applications.

The door panel is made up of a robust, steel reinforced stretch-frame, holding pressure cast polyurethane foam between outer coatings.

The reinforced stretch-frame is 5 mm thick steel with anchor profiles reinforcing locks, hinges and mountings.

Four different corner sealing joints placed around the door. The rubber sealing system provides insulation and tightness tested values according to European Standards.

Product guidance - As Standard

Arrangement:

Bi-folding panel doors.

Door leaf:

Steel reinforced stretch-frame, with pressure cast polyurethane foam between outer skins.

Finish:

PVS2.

Sealing system:

1.5 m³/m²/h to 150 Pa.

Options

Other requirements:

- Personnel entry doors.
- Window grilles.
- Door stops.

Product specification

Manufacturer

- Name: HAG Ltd. - The Door Specialists
- Web: www.hag.co.uk
- Email: info@hag.co.uk
- Tel: +44 (0)800 072 3444

[HAG Ltd. - The Door Specialists](#)



HAG Ltd. - The Door Specialists
1 Oak Lane
Fishponds
Bristol
BS5 7UY

Tel: +44 (0)800 072 3444

www.hag.co.uk
info@hag.co.uk



- Fax: +44 (0)117 965 7773

- Address: 1 Oak Lane, Fishponds, Bristol BS5 7UY

Product reference	Roller Shutter Industrial Door Q Door
Outer skins	Hot dip galvanized steel with powder coat finish - Insert colour requirements.
Opening	Inward Outward
Operation	Electrical - 3 phase with push button control unit and edge sensors, closing time 8 seconds. Manual
Other requirements	Personnel doors Personnel entry doors Windows