



Stack Door

Generated on 18.01.2020

Detailed description

Self-locking, vertically stacking commercial security grille.

Features and benefits:

- Achieves 80% visibility.
- Can be curved if required to suit project requirements.
- Features vertical lift operation.
- Has a small stack zone, making the grille suitable for limited headroom applications.
- Automatically self-locking and cannot be forced upwards.
- A manual override is included to operate the grille in the event of a power failure. This is usually operable from one side only - consult manufacturer for details.

Applications:

- Can be used for large spans in various applications, including:
- Securing automatic revolving doors.
- High use commercial car parks
- Retail premises.
- Airports.
- Bars and restaurants.
- Kiosks.
- Curved apertures.

Product guidance - As Standard

Construction:

Curtain: Solid steel vertical pins secured to horizontal steel profiles.

Guides and bottom rail: Heavy duty extruded aluminium guide rails with a reinforced extruded aluminium bottom rail (corner applications do not require guide rails).

Options

Colour/ Finish (curtain):

Please note that the vertical pins cannot be powder-coated.

Operation:

- Single phase electric:

A tubular motor with limit switches and thermal cut out to prevent

HAG Ltd. - The Door Specialists



HAG Ltd. - The Door Specialists

1 Oak Lane
Fishponds
Bristol
BS5 7UY

Tel: +44 (0)800 072 3444

www.hag.co.uk
info@hag.co.uk



overheating. Draws 240 V (0.5–2.5 A) dependent upon the shutter size. Provision of a 3 A fused spur is required for installation.

- Three phase electric:

The design of the model will alter for a three phase operation. Electrical requirements are dependent on usage, consult manufacturer for further details.

Product specification

Manufacturer

- Name: HAG Ltd. - The Door Specialists
- Web: www.hag.co.uk
- Email: info@hag.co.uk
- Tel: +44 (0)800 072 3444
- Fax: +44 (0)117 965 7773
- Address: 1 Oak Lane, Fishponds, Bristol BS5 7UY

Product reference Stack Door

Type Car park
Compact
Corner
Curved
Standard

Size

- Height []

- Span (width) []

Curtain

- Design Brick bond style
Inline

- Colour/ Finish Stainless steel
Polyester powder-coated, RAL/
BS - Insert requirement.

Operation Single phase electric - See
'Options' for details.
Three phase electric - See
'Options' for details.

Controls Rocker switch
Standard security key switch
Special order - On request,
consult manufacturer for
details.



ribaproductselector.com

A building products library for construction industry professionals

NBS Plus

**Accessories/ Other
requirements**