



Tectite Thermostatic Mixing Valves

Generated on 14.07.2020

Detailed description

Thermostatic mixing valves with Tectite push-fit connections. Maximum 10 bar static pressure (3 bar with PEX and PB pipework).

Two-year guarantee. WRAS-approved. TMV 2 and TMV 3 in compliance with BS 7942 and NHS Estates Model Engineering Specification D 08.

Product specification

Manufacturer

- Name: Pegler Yorkshire
- Web: www.pegleryorkshire.co.uk
- Email: uk.sales@pegleryorkshire.co.uk
- Tel: +44 (0)1302 560560
- Fax: +44 (0)1302 367661
- Address: St Catherine's Avenue, Doncaster, South Yorkshire DN4 8DF

Product reference Tectite Thermostatic Mixing Valves

Type
5A1560 15 mm TX402
5A1561 22 mm TX402
5A1562 15 mm TX402UA
5A1563 22 mm TX402UA
5A1564 15 mm TX402UAX
5A1565 22 mm TX402UAX

Accessories
[None]
[5A1156 15 mm filter kit TMV 3/2] - Tectite push-fit connections x flat face union.
[5A1157 22 mm filter kit TMV 3/2] - Tectite push-fit connections x flat face union.



Pegler Yorkshire
St Catherine's Avenue
Doncaster
South Yorkshire
DN4 8DF

Tel: +44 (0)1302 560560

www.pegleryorkshire.co.uk
uk.sales@pegleryorkshire.co.uk



ribproductselector.com

A building products library for construction industry professionals

NBS Plus