



XPress Carbon

Generated on 21.08.2019

Detailed description

XPress carbon fittings are available in sizes from 15–108 mm and they incorporate a black Ethylene Propylene Diene Monomer (EPDM) 'O' ring.

Applications:

- Designed for use in vented and unvented closed circuit heating and chilled water applications.
- Can be use with SC645 tube and is also suitable for use on wet fixed sprinkler systems.
- Incorporating a unique and timesaving Leak Before Press (LBP) design to instantly identify un-pressed joints.

The range includes:

- Straight and straight reduced couplings.
- Straight male and female connectors.
- Elbows and street elbows.
- Equal tees.
- Tee, reduced branches.
- Stop ends.
- Union connector.

Ten year guarantee. WRAS and DVGW (GW541) approved plus international approvals, including several for Fire Protection applications.

Product guidance - As Standard

Service temperature/ pressure (15–108 mm):

-35°C to +135°C: 16 bar.

Product specification

Manufacturer

- Name: Pegler Yorkshire
- Web: www.pegleryorkshire.co.uk
- Email: uk.sales@pegleryorkshire.co.uk
- Tel: +44 (0)1302 560560
- Fax: +44 (0)1302 367661
- Address: St Catherine's Avenue, Doncaster, South Yorkshire
DN4 8DF

Pegler Yorkshire



Pegler Yorkshire
St Catherine's Avenue
Doncaster
South Yorkshire
DN4 8DF

Tel: +44 (0)1302 560560

www.pegleryorkshire.co.uk
uk.sales@pegleryorkshire.co.uk

