



Bona Hard Wax Oil

Generated on 19.08.2019



Detailed description

A balanced blend of natural oils and waxes for surface treating untreated wooden floors and other interior woodwork. Bona Hard Wax Oil impregnates the wood and creates a durable superficial film with excellent resistance to water and spills. Can be combined with a coloured version of Bona Craft Oil.

Advantages:

- Extreme water resistance.
- Rapid drying, fast working process.
- Inhibits risk of side-bonding.
- High coverage rate.
- Safe for application on children's toys and countertops, EN 71-3 compliant.

Product guidance - As Standard

Composition:

Modified vegetable oils and waxes.

Solids content:

48%.

Dilution:

Do not dilute.

Coverage:

20–24 m²/L per coat.

Drying time (20°C, 60%RH):

- Between coats: 6–8 hours.
- Light use: 16 hours.

Options

Sheen (at 60°):

- Matt: 10.
- Silk matt: 25.

Product specification

Manufacturer

Bona Limited

Bona Limited
6 Thornton Chase
Linford Wood
Milton Keynes
Buckinghamshire
MK14 6FD

Tel: +44 (0)1908 525150

www.bona.com
info.uk@bona.com



- Name: Bona Limited
- Web: www.bona.com
- Email: info.uk@bona.com
- Tel: +44 (0)1908 525150
- Fax: +44 (0)1908 311677
- Address: 6 Thornton Chase, Linford Wood, Milton Keynes, Buckinghamshire MK14 6FD

Product reference Bona Hard Wax Oil

Finish Matt
Silkmat

Number of coats One
Two