



easy tex

Generated on 08.04.2020

Detailed description

A non-woven polyester separation and protection layer.

It is intended to be used:

- Where there is a risk of the waterproof membrane vibrating ("drum effect").
- To remove undulations from insulation.
- Where the substrate is uneven.
- Where the substrate includes low melting point bitumen.

HERTALAN®

Carlisle Construction Materials Ltd-
HERTALAN - RESITRIX
Lancaster House
Concorde Way
Millennium Business Park
Mansfield
Nottinghamshire
NG19 7DW

Tel: +44 (0)1623 627285

www.hertalan.co.uk
info.uk@ccm-europe.com

Product guidance - As Standard

Thickness:

3 mm.

Weight:

300 g/m².

Options

Roll length:

Available in various lengths.

Product specification

Manufacturer

- Name: Carlisle Construction Materials Ltd-HERTALAN - RESITRIX
- Web: www.hertalan.co.uk
- Email: info.uk@ccm-europe.com
- Tel: +44 (0)1623 627285
- Fax: +44 (0)1623 652741
- Address: Lancaster House, Concorde Way, Millennium Business Park, Mansfield, Nottinghamshire NG19 7DW

Product reference easy tex

Width 1 m
2 m



ribproductselector.com

A building products library for construction industry professionals

NBS Plus