



Hortag

Generated on 21.08.2019

Detailed description

Incorporating Lytag horticulture aggregate (Hortag) within the build-up can greatly reduce the loading on the structure as well as aiding in the moisture transfer.

Lytag as a secondary aggregate will omit the need for natural aggregate within the Green roof build-up while providing greater water dispersion and attenuation, a suitable medium for sustaining vegetation and reducing the overall weight.

Applications:

Intensive, extensive, or simple intensive green roof systems.

ISO 9001, 14001 and 18001 certificates, BES 6001 certificate (excellent rating).

Product guidance - As Standard

Technical characteristics:

- Grade: 8/14 mm.
- Loose bulk density: 750 kg/m³ (oven dry).
- Water absorption: 30 minutes: 12.4% by mass, 24 hours: 15.2% by mass.

Density:

862 kg/m³ based on a moisture content of 15%. This may however vary slightly. Bulk densities are also available.

Product specification

Manufacturer

- Name: Aggregate Industries – Lytag
- Web: www.aggregate.com/our-businesses/lytag
- Email: sales@lytag.com
- Tel: +44 (0)207 4995242
- Fax: +44 (0)1904 720181
- Address: Drax Power Station, Selby, North Yorkshire YO8 8PH

Product reference Hortag

LYTAG[®]
lightweight solutions

Aggregate Industries – Lytag
Drax Power Station
Selby
North Yorkshire
YO8 8PH

Tel: +44 (0)207 4995242

www.aggregate.com/our-businesses/lytag
sales@lytag.com



ribaproductselector.com

A building products library for construction industry professionals

NBS Plus