



Safe-R SR/FB

Generated on 16.12.2019

Detailed description

Safe-R Framing Board SR/FB is designed for use with steel or timber frame applications up to 18 m in height. With a Euroclass B Fire Classification the framing board can be used between studs or as an insulated sheathing board. Using SR/FB provides good U-values and improved thermal bridging detailing.

Product guidance - As Standard

Standard:

To BS EN 13166.

Sheet size:

2400 x 1200 mm.

Edge profile:

Straight edge.

Thermal conductivity (lambda value):

0.020–0.021 W/m·K

Product specification

Manufacturer

- Name: Xtratherm UK Ltd
- Web: www.xtratherm.com
- Email: info@xtratherm.com
- Tel: +44 (0)371 2221033
- Fax: +44 (0)371 2221044
- Address: Park Road, Holmewood Enterprise Park, Chesterfield, Derbyshire S42 5UY

Product reference Safe-R SR/FB

Thickness
40 mm
50 mm
60 mm
75 mm
80 mm
100 mm
120 mm

Xtratherm UK Ltd
Park Road
Holmewood Enterprise Park
Chesterfield
Derbyshire
S42 5UY

Tel: +44 (0)371 2221033

www.xtratherm.com
info@xtratherm.com



ribproductselector.com

A building products library for construction industry professionals

NBS Plus