



Thin-R XT/Walk-R

Generated on 22.08.2019

Detailed description

Loft decking board, composite of high performance polyisocyanurate (PIR) insulation with tough oriented-strand board (OSB) board that provides safe access into insulated roof spaces.

XT/Walk-R maintains very high insulation values and complies with health and safety guidelines.

Whether building new or upgrading, due consideration towards the energy efficiency of a home can have many benefits, including reduced energy costs and improved living conditions. But how do you allow safe access to this space, water tanks, services and fittings? XT/Walk-R allows safe access to the roof space, water tanks, services and fittings as well as improved insulation of the attic space.

Product guidance - As Standard

Standard:

Insulation to BS EN 13165.

Board size:

1200 x 600 mm.

Thickness:

- PIR insulation: 75 mm.
- Oriented strand board (OSB): 11 mm.

Thermal conductivity (lambda value):

Insulation: 0.022 W/m·K.

Product specification

Manufacturer

- Name: Xtratherm UK Ltd
- Web: www.xtratherm.com
- Email: info@xtratherm.com
- Tel: +44 (0)371 2221033
- Fax: +44 (0)371 2221044
- Address: Park Road, Holmewood Enterprise Park, Chesterfield, Derbyshire S42 5UY

Product reference Thin-R XT/Walk-R

[Xtratherm UK Ltd](#)

Xtratherm UK Ltd
Park Road
Holmewood Enterprise Park
Chesterfield
Derbyshire
S42 5UY

Tel: +44 (0)371 2221033

www.xtratherm.com
info@xtratherm.com



ribaproductselector.com

A building products library for construction industry professionals

NBS Plus

Edge profile

Straight edge
Tongue and groove