



## 9156A Overhead Door Closer

Generated on 17.01.2020

### Detailed description

The Allgood type 9156A figure 6 door closer is a heavy-duty door closer with fully adjustable power and adjustable backcheck, the closing speed is fully adjustable with independent latch action.

Units are designed for opening face fixing on internal and external wood and metal doors.

### Performance:

- Independently tested and complies with the requirements of BS EN 1154.
- Classification coding 3-8-2/4-1-1-3.
- CE marked certificate.
- Type 9156A has been included in third party testing on timber fire door assemblies to BS EN 1634-1 and BS 476-22. Providing fire resistance for 120 minutes.
- Type 9156A & 9156ADC units are UL listed R11296 and Type 9156A unit is Certifire CF104 approved, for use on certain latched and unlatched assemblies and single and double doors.

### Power Classification:

Power size: 2-4

Note: The hold open version is not suitable for use with fire doors

### Product specification

#### Manufacturer

- Name: Allgood plc
- Web: [www.allgood.co.uk](http://www.allgood.co.uk)
- Email: [info@allgood.co.uk](mailto:info@allgood.co.uk)
- Tel: +44 (0)20 7387 9951
- Address: 18 Holborn, London EC1N 2LE

**Product reference** 9156A  
9156ADC - Delayed closing version.  
9156ASO - Hold open version.

**Closer Casing finish** BF - Simulated bronze.  
MP - Modric polished etched and anodized.  
PS - Plated polished stainless steel finish.  
SS - Plated stainless steel finish.

Allgood plc



Allgood plc  
18 Holborn  
London  
EC1N 2LE

Tel: +44 (0)20 7387 9951

[www.allgood.co.uk](http://www.allgood.co.uk)  
[info@allgood.co.uk](mailto:info@allgood.co.uk)



**Accessories**

[Not required]

[Ø156FN] - Alternative Figure 6 face fixing bracket.

[Brackets and plates for metal doors]