



9000 Series Access Panel

Generated on 06.07.2020

Detailed description

The 9000 series range of hinged steel access panels provides access into sealed plasterboard or sandwich panel (demountable) wall and ceiling systems where access to mechanical and electrical services is required.

The welded metal frame holds a metal door tray which is hinged via fully adjustable concealed hinges and is held closed by either a push catch ([PC], not available for 1FR panel) or a security sealed key lock (SL). The door then opens towards the user.

The door is removable if damage occurs or during installation.

Panels are manufactured either as fully concealed so that after installation only a 2 mm wide door line is visible (BF), or alternatively, manufactured for retrofitting where the 25 mm picture frame surround is visible (PF). The PF type is also available with a modified frame for installation into 60 mm sandwich panel demountable structure. A constant gap is maintained between the door and frame by the fully adjustable hinge and dome location system.

Panels are supplied powder coated semi-gloss white all over as standard but can be supplied using plastic coated steel or stainless steel. Anti-bacterial paint is also available as an optional extra.

Customization of the access panel may be possible including alternative sizes, lock and paint colours, consult manufacturer for details.

Product guidance - As Standard

Frame depth:

Overall frame depth is 76.5 mm.

Options

Product reference:

- 9000/BF/PC or SL:

- Frame: 1.2 mm thick, factory welded electro-galvanized carbon steel with concealed beaded frame (BF) for plaster finishing. Finished powder coated semi-gloss white all over and fitted with rubber compressible gasket to all sides.
- Door: 0.9 mm thick electro-galvanized carbon steel flush door tray fitted with fully adjustable hinges and finished powder coated semi-gloss white all over as standard.
- Locks: Non fire rated types: Concealed push catches (PC) or security sealed lock (SL). Fire rated types: Security sealed lock (SL). Both types are fitted to the rear of the frame/door.

- 9000/PF/PC or SL:



Profab Access Ltd
Units C&D Riversdale House
Riversdale Road
Carlyon Road Industrial Est
Atherstone
Warwickshire
CV9 1FA

Tel: +44 (0)1827 718222

www.profabaccess.com
technical@profabaccess.com



As above options but with visible 25 mm picture frame surrounding the retro fitting. This type is also available with a modified frame depth for installation into 60 mm sandwich panel demountable structure.

Fire performance:

One (1FR) hour fire resistance tested to BS 476-22.

Size:

9000 series panels can be manufactured in any size from 150 x 150 mm up to a maximum of 600 x 1200 mm in single door configuration. Double (DS) and multiple door (CA) designs are also available. Consult manufacturer for details.

Product specification

Manufacturer

- Name: Profab Access Ltd
- Web: www.profabaccess.com
- Email: technical@profabaccess.com
- Tel: +44 (0)1827 718222
- Fax: +44 (0)1827 721092
- Address: Units C&D Riversdale House, Riversdale Road, Carlyon Road Industrial Est, Atherstone, Warwickshire CV9 1FA

Product reference 9000/BF/PC
9000/BF/SL
9000/PF/PC
9000/PF/SL
9000/BF/PC/1FR
9000/BF/SL/1FR
9000/PF/PC/1FR
9000/PF/SL/1FR

Size 300 x 300 mm
450 x 450 mm
600 x 600 mm
600 x 1200 mm