



Fade®

Generated on 11.07.2020

Detailed description

A high-quality plastering solution that absorbs unwanted noise in a wide range of environments. It is an acoustic solution that can be applied to walls and ceilings, with highly absorbent qualities to allow for optimum acoustic control in large, commercial spaces.

The system consists of a mineral fibre board which is overlaid with acoustical plaster. For curved, domed or vaulted surfaces, a mineral fibre board with a lower density is used, meaning that it can bend without splitting. Can be installed directly onto an existing ceiling grid or on a suspended steel construction, and does not require a layer of plasterboard.

Advantages:

- Up to class 'A' acoustic absorption performance.
- Three-step installation process – quick and easy to install.
- Easy to repair and maintain.
- Flexible to your design.
- Colour matching available.
- M1 emission class for building material.

Applications:

Can be installed in any internal area which requires seamless sound absorption without spoiling the aesthetic design. It is ideal for use in commercial and domestic venues such as auditoriums, retail and healthcare environments, leisure facilities, museums and offices.

While the system can be applied to horizontal and vertical surfaces, it is not recommended to use within touching distance: i.e. within 2.4 m of standing floor level.

Product guidance - As Standard

Acoustic performance:

NRC: Up to 1.0 (Class A).

Fire rating (EN 13501-1):

A2-s1, d0.

Options

Colour/ Finish:

Can also be supplied in a range of RAL or NCS colours. Consult manufacturer for information.

Thickness:

CMS Danskin Acoustics



CMS Danskin Acoustics

Unit 2
Lyncastle Road
Appleton Thorn
Warrington
Cheshire
WA4 4SN

Tel: +44 (0)1925 577711

www.cmsdanskin.co.uk
info@cmsdanskin.co.uk



Other thicknesses are available on request; consult manufacturer and insert requirements.

Product specification

Manufacturer

- Name: CMS Danskin Acoustics
- Web: www.cmsdanskin.co.uk
- Email: info@cmsdanskin.co.uk
- Tel: +44 (0)1925 577711
- Fax: +44 (0)1925 577733
- Address: Unit 2, Lyncastle Road, Appleton
Thorn, Warrington, Cheshire WA4 4SN

Product reference Fade®

Colour/ Finish Albus - A lightly textured medium grain finish available in off-white to suit design requirements.
Albus Plus - An ultra-smooth, fine grain white finish. Sanded or trowelled to achieve a highly aesthetic acoustic solution.

Thickness 25 mm
40 mm