



Flexi Everyday - Flexi Foot

Generated on 14.07.2020

Detailed description

Support system with strut for supporting outdoor equipment. Manufactured from milled, sieved and graded recycled rubber, bound with high-quality adhesive, and compression-moulded.

Features and benefits:

- Non-penetrative support.
- Flexible, and can accommodate late design changes.
- Fast and simple installation.
- Available in four sizes to suit project requirements.
- Supplied with an integrated 21 x 41 x 1.5 mm steel strut which has been fully bonded to the foot with industrial strength adhesive, and is stronger than aluminium alternatives.
- The dense nature of these products makes them suitable for various lightweight building services supports.
- Drainage slots are moulded to the underside of the foot for rainwater run-off.
- Suitable for internal and external environments between -40°C and 80°C .
- Robust, heavy-duty and high-quality materials used.
- Channel is compatible with industry-standard fixings and fixtures.

Applications:

Suitable for the everyday support and installation of a variety of outdoor equipment, including:

- Pipework, including small flow-and-return installations.
- Lightweight cable baskets and cable trays at low level.
- Electrical containment.
- Single fan air-conditioning units.
- Air source heat pumps.
- Solar thermal and solar photovoltaic on flat roof installations.

Product guidance - As Standard

Overall size (l x w x h):

- FF-250-S: 250 x 185 x 100 mm.
- FF-400-S: 400 x 185 x 100 mm.
- FF-600-S: 600 x 185 x 100 mm.
- FF-1000-S: 1000 x 185 x 100 mm.

Flexi Support Systems from Pump House



Flexi Support Systems from Pump House

Glaisdale Drive East

Nottingham

NG8 4LY

Tel: +44 (0)115 9005858

www.flexisupportsystems.co.uk
sales@flexisupportsystems.co.uk



Material:

- Foot: Styrene-butadiene rubber (SBR) to BS 7188 and BS EN 1176-7. UV-stabilized.
- Strut: Steelwork manufactured in accordance with BS EN 102191, and hot-dip galvanized to BS EN ISO 1461.

Weight:

- FF-250-S: 2.8 kg.
- FF-400-S: 4.6 kg.
- FF-600-S: 7.6 kg.
- FF-1000-S: 12 kg.

Technical characteristics:

- Density: 1 kg/cm³.
- Maximum load: FF-250-S: 175 kg; FF-400-S: 280 kg; FF-600-S: 420 kg; FF-1000-S: 700 kg. Tested with a 4:1 safety ratio.

Product specification

Manufacturer

- Name: Flexi Support Systems from Pump House
- Web: www.flexisupportsystems.co.uk
- Email: sales@flexisupportsystems.co.uk
- Tel: +44 (0)115 9005858
- Address: Glaisdale Drive East, Nottingham NG8 4LY

Product reference	FF-250-S - With 250 mm strut.
	FF-400-S - With 400 mm strut.
	FF-600-S - With 600 mm strut.
	FF-1000-S - With 1000 mm strut.