



TopX Acrylic Glass Effect Surfaces

Generated on 22.10.2019

Detailed description

2 mm scratch, scour and chemical resistant Senoplast acrylic, high gloss laminated sheet which creates an authentic glass appearance with a surface depth of colour and gloss effect. Laminated onto medium density fibreboard (MDF) and available in a range of colours and finishes.

Features and benefits:

- Scratch and scour resistant.
- High chemical resistance.
- Increased safety in 'glass style' applications.
- High UV resistance.
- Cuts and machines cleanly.
- High impact strength.
- Face can be machined - meaning and edges can be chamfered.
- Supplied laminated with a polyurethane (PE) protective film.
- No additional polishing is required.
- Laminated with balancer.
- Matching 2 mm balancer is available for all finishes.
- Tested to FIRA 6250:2005.
- FSC® certified.

Applications:

Suitable for a variety of internal residential and commercial uses, including:

- Kitchen, bedrooms, bathrooms and living room applications.
- Furniture doors and internal furniture components.
- Shop-fitting.
- Exhibition walls and furniture.
- Internal fit out.

Can be cleaned with normal cleaning agents. The use of abrasive effect cleaning agents and scouring agents can cause damage.

Product guidance - As Standard

Board material:

Medium density fibreboard (MDF).

Board size (l x w x t):

2800 x 1300 x 15 mm.

Decorative Panels Lamination Ltd



Decorative Panels Lamination Ltd

Decorative Panels Holdings Ltd
Century house
Premier way
Elland
West Yorkshire
HX5 9HF

Tel: +44 (0)1484 658341

www.decorativepanels.co.uk
info@decorativepanels.co.uk



Surface thickness:

2 mm.

Technical characteristics (to FIRA 6250:2005):

- Resistance to impact: 5 (no visible change, with dropped steel ball).
- Scrape resistance: 5 (no visible change to surface or substrate penetration).
- Resistance to dry heat: 5 (no visible change at 85°C; slight mark at 100°C).
- Resistance to wet heat: 5 (no visible change at 55°C, 70°C and 85°C).
- Resistance to staining: 5 (no visible change).
- Haze test: No damage (at 63 rubs).
- Gloss measure: 90.6% at 20°C; 94.3% at 60°C.

Options

Colour/ Finish:

Finish options are dependent on colour choice. Consult manufacturer for information.

Product specification

Manufacturer

- Name: Decorative Panels Lamination Ltd
- Web: www.decorativepanels.co.uk
- Email: info@decorativepanels.co.uk
- Tel: +44 (0)1484 658341
- Address: Decorative Panels Holdings Ltd, Century house, Premier way, Elland, West Yorkshire HX5 9HF

Product reference TopX Acrylic Glass Effect Surfaces

Colour/ Finish []

Balancer Not required
Required - Matching 2 mm balancers available for all finishes; consult manufacturer for information.