



IRO External Cladding

Generated on 14.07.2020

Detailed description

Inspired by the Japanese process of Yakisugi, IRO is 100% eco-friendly, UV-stable and HVOC-free. As IRO is heat enhanced and coated in Rubio Monocoat cream, it is more durable and offers a more striking grain appearance than its traditional cladding and decking counterparts. Available in 15 shades, kiln dried, charred, brushed and brown treated.

Applications:

External horizontal and vertical cladding.

Product guidance - As Standard

Section size:

- Nominal size: 25 x 150 mm.
- Finished size: 22 x 145 mm.

Species:

Homegrown larch.

Profile:

Shiplap and square edge.

Options

Colour:

After about two years, the pearl effect will gradually fade. On average, the colour on vertical surfaces lasts between two and five years.

Product specification

Manufacturer

- Name: BSW Timber Ltd
- Web: www.bsw.co.uk
- Email: marketing@bsw.co.uk
- Tel: +44(0)8005878887
- Fax: +44 (0)800 587 8897
- Address: Carlisle Sawmills, Cargo, Carlisle, Cumbria CA6 4BA

Product reference IRO External Cladding



BSW Timber Ltd
Carlisle Sawmills
Cargo
Carlisle
Cumbria
CA6 4BA

Tel: +44(0)8005878887

www.bsw.co.uk
marketing@bsw.co.uk



Board length	3300 mm 3600 mm
Colour	Charcoal Chestnut Claret Dolphin Dragon fruit Driftwood Forest Lagoon Mountain Natural Piglet Poppy Sunflower Sunset Woodland