



PB Pedestal System

Generated on 20.11.2019

Detailed description

Screwjack pedestal system.

Features and benefits:

- Pedestal height: 15–965 mm.
- Copolymer polypropylene pedestal. Resistant to weather, UV, chemical products. Electrically non-conductive. Not susceptible to galvanic corrosion.
- Uses 80% recycled PPC, 20% talc plus UV black masterbatch and is 100% recyclable.
- Sloping substrates: Optional, wedge-type slope corrector for placement under pedestal.
- Resistant to UV light, weather, sea salt and almost all chemicals.
- Application temperature range: -30 to +90°C.

Usage:

Support for outdoor terraces with any kind of materials; timber decking, stone, ceramic, composite materials, metal, fibreglass grid. Can be placed on any stable substrate; also over insulation panels.

Product guidance - As Standard

Adjustment:

– Height:

Threaded for assembly and height adjustment.

– Pitch:

Slope connector BC-PH5 is placed under the base of the pedestal. Consisting of two cylindrical parts, it allows compensation of 1–5% slopes by simply rotating the devices. Thickness: + 12 mm to be added to the adjustment height of the pedestal.

Compression:

Breaking load can vary depending on configuration and product type; consult literature for details.

Options

Accessories:

Different Buzon accessories can be clipped to the head of the pedestal according to the material used by manufacturers of terraces, podiums and temporary exhibitions.

Buzon UK Ltd



Buzon UK Ltd

Unit 6

Teddington Business Park

Station Road

Teddington

Middlesex

TW11 9BQ

Tel: +44 (0)20 8614 0874

www.buzonuk.com

info@buzonuk.com



Product specification

Manufacturer

- Name: Buzon UK Ltd
- Web: www.buzonuk.com
- Email: info@buzonuk.com
- Tel: +44 (0)20 8614 0874
- Fax: +44 (0)20 8977 0825
- Address: Unit 6, Teddington Business Park, Station Road, Teddington, Middlesex TW11 9BQ

Product reference PB Pedestal System

Substrate []

Pedestal

- Type PB-0 - Fixed height 15 mm.
PB-01 - Adjustable 28–42 mm – comprises two-piece head and base.
PB1 - Adjustable 42–60 mm – comprises two-piece head and base.
PB2 - Adjustable 60–90 mm – comprises two-piece head and base.
PB3 - Adjustable 90–145 mm – comprises two-piece head and base.
PB4 - Adjustable 145–245 mm – comprises two-piece head and base.
PB5 - Adjustable 230–315 mm – comprises head PB3 plus base PB4 and one sleeve C1-PB4.
PB6 - Adjustable 285–367 mm – Pedestal PB4 plus one sleeve C1-PB4.
PB7 - Adjustable 365–485 mm – Pedestal PB4 plus two sleeves C1-PB4.
PB8 - Adjustable 452–605 mm – Pedestal PB4 plus three sleeves C1-PB4.
PB9 - Adjustable 537–725 mm – Pedestal PB4 plus four sleeves C1-PB4.
PB10 - Adjustable 620–845 mm – Pedestal PB4 plus five sleeves C1-PB4.
PB11 - Adjustable 705–965 mm – Pedestal PB4 plus six sleeves C1-PB4.
To suit levels as drawing

Accessories [Not required]
[BC-PH-5] - Slope corrector.
[Standard wood batten]
[Tile separator]
[Twinson]
[Under study]
[Werzalit]



ribproductselector.com

A building products library for construction industry professionals

NBS Plus