



Floor/ Roof Light - NAG-RC254-100B

Generated on 22.10.2019



Detailed description

Pre-cast concrete floor/ roof lights with circular lenses.

Benefits:

- Cast in a controlled environment giving a consistent finish.
- Can speed up on-site installation.
- Can be fitted during very cold weather as they are already cured.
- Minimal possibility of shrinkage.

Product guidance - As Standard

Thickness:

100 mm.

Blocks:

- Size: 190 mm diameter x 100 mm thick.
- Centres: 254 mm.

Weight:

1.7 kN/m² (170 kg/m²).

Fire-rating:

One hour (concrete grillage).

U-value:

4.22 W/m²K.

Light transmittance:

25%.

Options

Size:

- Span:

Maximum spans are dependent on the loading conditions, consult manufacturer's literature for information.

- Bearing:

The minimum bearing is dependent on the loading conditions. The bearing size must be increased by 25 mm if an asphalt tuck is specified, consult

New Age Glass Ltd
Unit 4
Phoenix Business Centre
Spur Road
Chichester
West Sussex
PO19 8PN

Tel: +44 (0)1243 790414

www.newageglass.co.uk
info@newageglass.co.uk



manufacturer's literature for information.

Product specification

Manufacturer

- Name: New Age Glass Ltd
- Web: www.newageglass.co.uk
- Email: info@newageglass.co.uk
- Tel: +44 (0)1243 790414
- Fax: +44 (0)1243 790415
- Address: Unit 4,Phoenix Business Centre,Spur Road,Chichester,West Sussex PO19 8PN

Product reference NAG-RC254-100B

Size

- Span []

- Bearing []

Edges Asphalt tuck
Standard

Perimeter waterproofing

- Bearing Perimeter Hydrophilic
Waterstop - Not suitable for
pre-cast units.
Standard

- Exposed concrete Natural
Rubberized bitumen hot
applied horizontal joint sealant

- Abutment and expansion joints One-part moisture curing, self
levelling joint sealant
Rubberized bitumen hot
applied horizontal joint sealant

Concrete reinforcement Carbon steel
Stainless steel

Glass lenses to BS EN 1051-1 Clear
Sandblasted