



## Absorber Ceiling Tile

Generated on 11.12.2019

### Detailed description

Acoustic panel which adheres to walls and ceilings, absorbing noise and providing an excellent performance rating. It has a glass mineral fibre core with a white speckled surface finish, includes bevelled edges. Suitable for schools, offices, music studios, lecture theatres and multi-purpose halls.

### Product guidance - As Standard

#### Size:

600 x 1200 x 20 mm.

#### Weight:

2.5 kg/m<sup>2</sup>.

#### Fire rating:

Class 0.

#### Sound absorption co-efficient (to BS EN ISO 354):

- 125 Hz: 0.10.
- 250 Hz: 0.30.
- 500 Hz: 0.80.
- 1000 Hz: 1.00.
- 2000 Hz: 1.00.
- 4000 Hz: 0.85.

### Product specification

#### Manufacturer

- Name: JCW Acoustic Supplies Limited
- Web: [www.acoustic-supplies.com](http://www.acoustic-supplies.com)
- Email: [sales@acoustic-supplies.com](mailto:sales@acoustic-supplies.com)
- Tel: +44 (0)1204 548400
- Fax: +44 (0)1204 366960
- Address: Units 32-34, Waters Meeting Development, Britannia Way, Bolton, Lancashire BL2 2HH

**Product reference** Absorber Ceiling Tile - 1101

#### JCW Acoustic Supplies Limited

Units 32-34  
Waters Meeting Development  
Britannia Way  
Bolton  
Lancashire  
BL2 2HH

Tel: +44 (0)1204 548400

[www.acoustic-supplies.com](http://www.acoustic-supplies.com)  
[sales@acoustic-supplies.com](mailto:sales@acoustic-supplies.com)



**ribaproductselector.com**

A building products library for construction industry professionals

**NBS Plus**