



Acoustic Batten JCW 80C

Generated on 11.12.2019

Detailed description

Timber floor batten laminated to a 9 mm thick acoustic resilient layer.

Features/ Benefits:

- Ideal for Robust Detail FFT-1 floating floor treatment for flooring types: E-FC-1, E-FC-2, E-FC-7, E-FS-1 and E-FS-2.
- Raised floor space can be used for installing services.
- Ideal for good impact sound improvement where height permits.
- In refurbishments, it is overlaid onto flat timber or concrete floors.

Product guidance - As Standard

Size (h x w x l):

80 x 42 x 1800 mm.

Weight:

2.9 kg.

Impact sound reduction:

rd Δ Lw = 31 dB.

Product specification

Manufacturer

- Name: JCW Acoustic Supplies Limited
- Web: www.acoustic-supplies.com
- Email: sales@acoustic-supplies.com
- Tel: +44 (0)1204 548400
- Fax: +44 (0)1204 366960
- Address: Units 32-34, Waters Meeting Development, Britannia Way, Bolton, Lancashire BL2 2HH

Product reference JCW 80C - 1470



JCW Acoustic Supplies Limited

Units 32-34
Waters Meeting Development
Britannia Way
Bolton
Lancashire
BL2 2HH

Tel: +44 (0)1204 548400

www.acoustic-supplies.com
sales@acoustic-supplies.com



ribaproductselector.com

A building products library for construction industry professionals

NBS Plus