



Acoustic Deck 28/32

Generated on 08.12.2019

Detailed description

P5 grade chipboard overlay or direct to joist board for concrete or timber floors. Comprises an 18 or 22 mm thick tongue and grooved board with a pre-bonded 10 mm thick resilient foam layer. Concrete floor applications comply with Robust Detail FFT-5 floating floor treatment for flooring types E-FC-1, E-FC-2 and E-FS-1.

Product guidance - As Standard

Size (w x l):

600 x 2400 mm.

Impact sound reduction:

- Timber direct to joist: 56 dB Ln,w.
- Concrete overlay: $\Delta L_w = 18$ dB.

Airborne sound improvement (timber direct to joist):

Rw + Ctr = 52 dB

Product specification

Manufacturer

- Name: JCW Acoustic Supplies Limited
- Web: www.acoustic-supplies.com
- Email: sales@acoustic-supplies.com
- Tel: +44 (0)1204 548400
- Fax: +44 (0)1204 366960
- Address: Units 32-34, Waters Meeting Development, Britannia Way, Bolton, Lancashire BL2 2HH

- Product reference**
- Acoustic Deck 28 - 1071 - 28 mm thickness; weight: 17.8 kg.
 - Acoustic Deck 32 - 1074 - 32 mm thickness; weight: 21.8 kg.



JCW Acoustic Supplies Limited

Units 32-34
Waters Meeting Development
Britannia Way
Bolton
Lancashire
BL2 2HH

Tel: +44 (0)1204 548400

www.acoustic-supplies.com
sales@acoustic-supplies.com



ribproductselector.com

A building products library for construction industry professionals

NBS Plus