



DOWSIL™ 796 PVC-U, Aluminium and Wood Silicone



Generated on 18.01.2020

Detailed description

DOWSIL™ 796 PVC-U, Aluminium and Wood Silicone Sealant is a one-part, low modulus, neutral curing silicone sealant specifically developed for the sealing of PVC-U, glass, glazed surfaces and brickwork. It is very popular for perimeter sealing applications of windows and doors.

Dow Silicones Belgium SPRL

Parc Industriel - Zone C

Rue Jules Bordet

Seneffe B-7180

Belgium

Tel: +44 (0)800 917 2071

Features:

www.consumer.dow.com/construction
jane.pfeil@dowcorning.com

- Good unprimed adhesion to a variety of substrates.
- Low modulus, high elasticity.
- 100% silicone polymer.
- Neutral cure.
- Low odour.
- Conforms to ISO 11600-F&G-25LM.
- Resistant to ozone, ultra-violet radiation and temperature extremes.

Product guidance - As Standard

Properties:

- At 23°C (73°F) and 50% RH:

- Application temperature: 5–40°C.
- Specific gravity: 1.52.
- Extrusion rate: 210 g/minute.
- Skin-over time: 15 minutes.
- Tack-free time: 35 minutes.
- Cure rate (1 day/ 3 days): 2.0/ 3.5 mm.

Options

Colour:

A range of standard colours. Custom colours also available.

Product specification

Manufacturer

- Name: Dow Silicones Belgium SPRL
- Web: www.consumer.dow.com/construction
- Email: jane.pfeil@dowcorning.com

Dow Silicones Belgium SPRL



ribaproductselector.com

A building products library for construction industry professionals

NBS Plus

- Tel: +44 (0)800 917 2071
- Fax: +32 64 888 950
- Address: Parc Industriel - Zone C, Rue Jules Bordet, Seneffe B-7180, Belgium

Product reference DOWSIL™ 796 PVC-U, Aluminium and Wood Silicone

Colour

- Anthracite
- Black
- Bronze
- Brown
- Cream
- Dark brown
- Golden oak
- Green
- Grey
- Oak
- Pine
- White