



Ashton Wall Mounted Canopy

Generated on 21.08.2019

Detailed description

Wall mounted aluminium framed canopy which is the ideal solution where a big span and projection are required in commercial settings, such as covering loading bays or other situations where protection from the elements is required, such as walkways between buildings or creating outdoor waiting or dining areas. Glass sides and sliding doors can also be added to create a completely enclosed outdoor room. Infrared heating and lighting can be incorporated, as well as post pads, signage, side fills, safety barriers and seating.

Product guidance - As Standard

Roof frame:

T6 grade structural aluminium.

Framework:

Main frame constructed from 150 x 150 x 2.5 mm aluminium box section featuring integral aluminium guttering.

Wall plate:

Extruded aluminium profile which fixes to the wall or steel bracket.

Finish:

Polyester powder coated.

Weather resistance:

During the manufacture of the polycarbonate panels, a layer of UV absorber is co-extruded on both sides which forms a barrier, providing high UV protection from the sun.

Guarantee:

The canopy carries a full ten-year insurance backed guarantee and has a life expectancy of 25 years.

Fire performance:

- Polycarbonate roof panels: Tested to most European standards; Class 1 to BS 476-7 and B-S1, d0 to BS EN 13501.
- Glass roof panels: Class 0.

Options

Cladding profiles:

Ornate clip-in aluminium cladding profiles that can be used to conceal power/ audio/ data cables or rainwater downpipes.

Able Canopies Ltd



Able Canopies Ltd
9-11 Faraday Close
Gorse Lane Industrial Estate
Clacton-on-Sea
Essex
CO15 4TR

Tel: +44 (0)800 389 9072

www.ablecanopies.co.uk
sales@ablecanopies.co.uk



Product specification

Manufacturer

- Name: Able Canopies Ltd
- Web: www.ablecanopies.co.uk
- Email: sales@ablecanopies.co.uk
- Tel: +44 (0)800 389 9072
- Fax: +44 (0)1255 425541
- Address: 9-11 Faraday Close, Gorse Lane Industrial Estate, Clacton-on-Sea, Essex CO15 4TR

Product reference Ashton Wall Mounted Canopy

Size

- Projection []
- Length []
- Height []

Glazing

- Material Structured polycarbonate, 35 mm thick - Includes UV protection, 1.2 W/mK.
Toughened glass, 8 mm thick
- Colour Not applicable - For toughened glass.
Clear - For polycarbonate only, 64% light transmission.
Opal - For polycarbonate only, 33% light transmission.

Framework

- Colour RAL 3000 Flame Red
RAL 5005 Signal Blue
RAL 5010 Gentian Blue
RAL 5012 Light Blue
RAL 6001 Emerald Green
RAL 6005 Moss Green
RAL 7001 Silver Grey
RAL 7016 Anthracite Grey
RAL 8007 Fawn Brown
RAL 9003 Signal White - Standard.
RAL 9005 Jet Black
RAL 9006 White Aluminium
Special order - Insert requirement.
- Cladding profiles Not required
Required



Accessories

- [None]
- [Glass sides and doors]
- [Infrared heaters]
- [Infrared lighting]
- [Post pads]
- [Safety barriers]
- [Seating]
- [Side fills]
- [Signage]