



Deko PF

Generated on 11.07.2020

Detailed description

Profile free partition which has similarities to Deko PV with slim aluminium profiles at floor, wall, and ceiling joints. The visible panel surface finish is achieved with discreet bevel edged boards which eliminate the need for visible profile joint trims. Only the discrete gypsum board joint trims, which give the partition character, are visible to the eye.

Features:

- Demountable and suitable for reuse.
- Doors and glazed modules can be incorporated
- Awarded the Danish Indoor Climate Label.
- Whiteboards, shelves and cabinets can be suspended from the partition.

Product guidance - As Standard

Type:

- PV 1090:

- Lining Gypsum board: 2 x 13 mm.
- Insulation: 50 mm.
- Airborne Sound Insulation (Rw): 42 dB.

- PV 1290:

- Lining Gypsum board: 4 x 13 mm.
- Insulation: 50 mm.
- Airborne Sound Insulation (Rw): 51 dB.

- PV 1490:

- Lining Gypsum board: 4 x 13 mm.
- Insulation: 75 mm.
- Airborne Sound Insulation (Rw): 58 dB.

Options

Doorsets:

- Door finish:

Three standard factory applied lacquers available along with optional special finishes.

Product specification

Indeqlås



Indeqlås

7 Duncan McIntosh Road
Wardpark North
Cumbernauld
Scotland
G68 0HH

Tel: +44 (0)1236 453000

www.indeqlas.co.uk
info@indeqlas.co.uk



Manufacturer

- Name: Indeglås
- Web: www.indeglas.co.uk
- Email: info@indeglas.co.uk
- Tel: +44 (0)1236 453000
- Fax: +44 (0)1236 453111
- Address: 7 Duncan McIntosh Road, Wardpark
North, Cumbernauld, Scotland G68 0HH

Product reference Deko PV

Type PV 1090 - 92 mm partition thickness, EI 30 fire resistance.
PV 1290 - 118 mm partition thickness, EI 60 fire resistance.
PV 1490 - 144 mm partition thickness, 60 minute fire resistance.

Abutments

- Base AGP-2 aluminium complete base section
SG-2 steel track with PFP face fixed laminate skirting
SG-2 steel track with face fixed 70 mm aluminium profile skirting
SG-2 steel track with ASFU face fixed angled aluminium skirting
- Joint Negative edge board on PF clips
Profile edge board on PF clips
- Head ALV-2 aluminium complete head section
AIP-1 single side aluminium head section
SG-2 steel track
- Wall start ALV-2 aluminium complete wall start section
SG-2 steel track with ASPV with PPL plastic insert
SG-2 steel track with ASPV with ASPD aluminium cover strip
- Corner 90-SHP-2 steel section + AIH-90 and AUH-90 aluminium cover trims
90-SHP-2 steel section + AIH-90 and ARUP-90 aluminium cover trims
135-SHH-2-135 section + AIH-135 and AUH-135 aluminium trims
135-SHH-2-135 section + AIH-135 and AUH-135 aluminium trims
- Finish** Satin anodized
White powder coated
RAL - Insert colour



Panel
12.5 mm plasterboard, unfinished
12.5 plasterboard with paint finish - Insert colour.
12.5 mm plasterboard with standard paper backed vinyl wallcovering
12.5 mm plasterboard with wallcovering

Doorsets

- Door frame Aluminium profile door frame with MDF insert core fixed with ASP aluminium joint section
Aluminium profile door frame with MDF insert core fixed with AIDU + ASIF aluminium architrave details

- Door width 686 mm - Single leaf.
786 mm - Single leaf.
826 mm - Single leaf, E30 fire rating.
926 mm - Single leaf, EI 30 fire rating.
1026 mm - Single leaf, EI 60 fire rating.
1126 mm - Single leaf.
861 mm - Double leaf.
As schedule ____

- Door finish NCS S 0502-Y White - Factory applied lacquer.
NCS S 1502-G50 Y Grey - Factory applied lacquer.
NCS S 3560-R80B Blue - Factory applied lacquer.

- Vision panel As drawing ____

Glazed panels [_____]

Accessories
[And]
[None]
[Shelving]
[Whiteboard]