



## Unilateral Two Single Pocket Doors into the same Pocket

Generated on 20.01.2020

### Detailed description

A sliding door system with a unilateral frame allowing two opposite-handed doors to slide into the same pocket. It requires the dimension of only a single frame whilst hosting two parallel doors, ideal when only short wall spaces are available in corridors and hall entrances, exploiting even the tightest of spaces.

### Features:

- Features:
- The door post, pocket and track assemble together and are inserted into the stud work as a complete unit which helps to ensure the door will run true and in line.
- Doors slides into the same pocket in the wall.
- Wide range of sizes to suit standard UK door sizes. Bespoke sizes available.
- Door panels up to 100 kg.
- Suitable for use with 35 or 44 mm thick doors.
- Doors, plasterboard and final architrave not included.

### Advantages:

- Quick and easy to assemble and install.
- Complete with full wooden jamb kit for a professional finish.
- Maintenance-free track and runners.
- Fully extractable track, no need to break into the wall should you ever want to remove it.
- Fully adjustable front and rear doorstep.
- Anti-warp door profile, ensuring a long-term, smooth sliding operation.
- Self-centring floor guide with anti-warp profile.

### Product guidance - As Standard

#### Finished wall thickness:

175 mm.

### Options

#### Size:

The following frame sizes (in mm) are available:

- 1952 x 2056: To suit 610 x 1981 mm door. Clearance: 585 x 1971



**Eclisse UK**  
Richmond House  
Occupation Lane  
Gonerby Moor  
Grantham  
Lincolnshire  
NG32 2BP

Tel: +44 (0)845 481 1977

[www.eclisse.co.uk](http://www.eclisse.co.uk)  
[info@eclisse.co.uk](mailto:info@eclisse.co.uk)



mm.

- 2204 x 2056: To suit 686 x 1981 mm door. Clearance: 661 x 1971 mm.
- 2456 x 2056: To suit 762 x 1981 mm door. Clearance: 737 x 1971 mm.
- 2608 x 2056: To suit 838 x 1981 mm door. Clearance: 813 x 1971 mm.
- 2882 x 2056: To suit 914 x 1981 mm door. Clearance: 900 x 1971 mm.
- 1982 x 2115: To suit 626 x 2040 mm door. Clearance: 600 x 2030 mm
- 2282 x 2115: To suit 726 x 2040 mm door. Clearance: 700 x 2030 mm.
- 2582 x 2115: To suit 826 x 2040 mm door. Clearance: 800 x 2030 mm.
- 2882 x 2115: To suit 926 x 2040 mm door. Clearance: 900 x 2030 mm.
- 3182 x 2115: To suit 1026 x 2040 mm door. Clearance: 1000 x 2030 mm.

#### Accessories:

- ECLISSE BIAS®: soft close anti-slam device with 40 kg. soft closing.
- ECLISSE BIAS® DS: Bi-directional safety soft close anti-slam device with 40 kg. soft closing.
- E-Motion: Linear motor open/close Can be operated by push button, infra red detector, remote control or radar sensor activator.
- Self closing mechanism: Open the door and it closes by itself.
- Soft close: Slide the door towards the close position and the soft close takes over.

#### Product specification

##### Manufacturer

- Name: Eclisse UK
- Web: [www.eclisse.co.uk](http://www.eclisse.co.uk)
- Email: [info@eclisse.co.uk](mailto:info@eclisse.co.uk)
- Tel: +44 (0)845 481 1977
- Fax: +44 (0)1476 560710
- Address: Richmond House ,Occupation Lane,Gonerby Moor,Grantham,Lincolnshire NG32 2BP

**Product reference** Unilateral Two Single Pocket Doors into the same Pocket

**Size** [  ]



**Door furniture**

OSO8 - Polished brass simple flush pull  
OSC4 - Antique brass simple flush pull.  
OSC2 - Polished chrome simple flush pull.  
OSC1 - Satin chrome simple flush pull.  
OSO3 - Polished brass bathroom lock.  
OSA - Antique brass bathroom lock.  
OSO1 - Polished chrome bathroom lock.  
OSS - Satin chrome bathroom lock.

**Accessories**

[Not required]  
[ECLISSE BIAS®]  
[ECLISSE BIAS® DS]  
[e-Motion motor]  
[Self closing mechanism]  
[Soft close]