



Armatherm™ Z Girt

Generated on 12.12.2019



Detailed description

Thermal bridging through standard cladding attachments has a large effect on the heat loss through a wall assembly.

Armatherm Z Girt helps to meet ASHRAE 90.1's requirements for continuous insulation by completely eliminating metal-to-metal contact and highly conductive elements associated with steel stud wall assemblies.

Features and benefits:

- Unrivalled thermal efficiency for clad walls.
- Provides continuous insulation meeting energy code requirements.
- Cost-effective in comparison with steel 'Z' girts with additional thermal solutions.
- As efficiency is increased, overall insulation thickness can be reduced.
- Can be easily shimmed for alignment.

Armatherm, a Brand of Armadillo Noise & Vibration Limited

Riverside Works
Brighton Street
Shipley
West Yorkshire
BD17 7EB

Tel: +44 (0)1274 591115

www.armatherm.co.uk
info@armatherm.com

Options

Height:

Available in three standards sizes; other sizes available on request.

Product specification

Manufacturer

- Name: Armatherm, a Brand of Armadillo Noise & Vibration Limited
- Web: www.armatherm.co.uk
- Email: info@armatherm.com
- Tel: +44 (0)1274 591115
- Address: Riverside Works, Brighton Street, Shipley, West Yorkshire BD17 7EB

Product reference Armatherm™ Z Girt

Height
50 mm
75 mm
100 mm



ribproductselector.com

A building products library for construction industry professionals

NBS Plus