



Point Elastic Sports Floor

Generated on 30.05.2020

Detailed description

The DYNAMIK Point Elastic sports floor comprises of a rubber crumb pad finished in a seamless polyurethane surface.

Seamless polyurethane brings the advantage of seamless installation. The surface finish will require periodic re-painting throughout its life in order to maintain its appearance and slip resistance.

The depth of the rubber crumb can be altered to achieve P1, P2 or P3 performance criteria.

Benefits:

- Meets the requirements of EN 14904.
- Multi functional sports floor.
- Seamless surface finish.
- Easy to clean.
- Large range of RAL colours available.

System includes:

- Polyurethane top coat.
- Polyurethane wear layer.
- Pore filler coat.
- Rubber crumb base layer, the depth of which depends on the specification.

Product guidance - As Standard

Technical properties (to BS EN 14904, P1-P3):

- Shock absorption: >25–>45%.
- Vertical deformation: <2.0–<3.5 mm.
- Ball rebound: >90%.
- Slip resistance: 80–110.
- Rolling load: 1500 N.

Product specification

Manufacturer

- Name: DYNAMIK Sport
- Web: www.dynamiksportsfloors.co.uk
- Email: info@dynamiksport.co.uk

DYNAMIK Sport



DYNAMIK Sport
Unit 10
Enterprise Trade Centre
Roman Farm Road
Bristol
BS4 1UN

Tel: +44 (0)117 3015120

www.dynamiksportsfloors.co.uk
info@dynamiksport.co.uk



- Tel: +44 (0)117 3015120
- Fax: +44 (0)117 3015101
- Address: Unit 10,Enterprise Trade Centre,Roman Farm Road
,Bristol BS4 1UN

Product reference Polyurethane Sports Floor
Colour [_____]
Accessories [None]
[Apparatus covers/ frames]
[Damp proof membrane]
[Giant Carpet Tile Floor Protection]
[Hockey skirting]
[Movement/ expansion joints]
[Solid skirting]
[Sports line marking]
[Ventilated skirting]