



Traffic|Wall® Phenolic

Generated on 11.07.2020

Detailed description

A parametric, modular, phenolic wall lining system. Comprising of solid grade laminate panelling and a self-healing steel frame.

Available in both standard and ASIAD approved system versions.

Benefits:

- For interior and exterior cladding application.
- Waterproof and high impact resistance; suitable for high-traffic or wet areas.
- Antibacterial properties.
- A simple, quick and cost-effective solution.
- Range of performances, textures and finishes available.

Components:

- Galvanized steel supports, with self healing properties.
- Concealed fixing hardware.
- Universal and panel-hanging brackets.
- Precision-machined panels.
- Steel vertical uprights.
- Joining sleeves.

Applications:

High traffic public areas within the commercial, educational, hospitality, infrastructure, residential and retail industry sectors.

Product guidance - As Standard

Fire certification:

Self-healing steel is fire-rated as standard.

Horizontal rail length:

2800 mm.

Battens:

Standard steel sections.

Corner detail:

Internal, External and End Cap Arrangements.

Flash gap detailing:

Inspired Surfaces



Inspired Surfaces

Inspired Surfaces
26 Brunel Road
Earlstrees Industrial Estate
Corby
Northamptonshire
NN17 4JW

Tel: +44 (0)1536 428789

www.inspiredsurfaces.com
enquiries@inspiredsurfaces.co.uk



Double-sided tape and flash gap strips.

Options

Material:

Available fire-rated. Consult manufacturer for information.

Product specification

Manufacturer

- Name: Inspired Surfaces
- Web: www.inspiredsurfaces.com
- Email: enquiries@inspiredsurfaces.co.uk
- Tel: +44 (0)1536 428789
- Address: Inspired Surfaces, 26 Brunel Road, Earlstrees Industrial Estate, Corby, Northamptonshire NN17 4JW

Product reference	Traffic Wall® Phenolic
Size	[]
Thickness	10 mm 12 mm 18 mm
Material	Solid grade laminate (SGL)
Colour/ Finish	[]
Foot detail	Adjustable feet Skirting