



MEDITE VENT

Generated on 18.11.2019

Detailed description

A high performance breathable external sheathing panel suitable for use in all types of timber frame structures.

Combining high racking strength in excess of Category 1 requirements with excellent vapour permeability and high weather resistance.

Features:

- Breathable sheathing panel suited to traditional timber frame and diffusion open systems.
- Very low water vapour diffusion factor to prevent condensation - μ 9.4 to EN 12572.
- High performance racking strength (category 1 to BS 5268).
- Zero added formaldehyde contributing to healthy environments.

Product guidance - As Standard

Size:

1197 x 2397 mm.

Thickness:

12 mm.

Fire rating:

Substrate is expected to achieve a fire class rating of Euro Class D.

Moisture content:

7% \pm 2% at the time of manufacture.

Options

Size:

Other dimensions are available by special request.

Product specification

Manufacturer

- Name: MEDITE SMARTPLY
- Web: www.mdfosb.com
- Email: info@mdfosb.com
- Tel: +44 (0)1322 424900

MEDITE SMARTPLY



MEDITE SMARTPLY

Persimmon House
Anchor Boulevard
Crossways Business Park
Dartford
Kent
DA2 6QH

Tel: +44 (0)1322 424900

www.mdfosb.com
info@mdfosb.com



ribaproductselector.com

A building products library for construction industry professionals

NBS Plus

- Fax: +44 (0)1322 424920

- Address: Persimmon House,Anchor Boulevard,Crossways
Business Park,Dartford,Kent DA2 6QH

Product reference MEDITE VENT